

# MCP300X 10-Bit Analog-to-Digital Converters

## Product Information



**The Microchip MCP300X family** of 10-bit analog-to-digital converters (ADCs) combines high performance and low power consumption in a small package – making it ideal for embedded control applications.

Consisting of the MCP3001, MCP3002, MCP3004 and MCP3008, the MCP300X family features a successive approximation register (SAR) architecture and an industry-standard SPI™ serial interface. Devices are available with 1, 2, 4 or 8 input channels and in PDIP, SOIC and TSSOP packages.

The MCP300X family offers existing Microchip customers added flexibility when incorporating analog inputs into their designs. The industry standard SPI interface allows 10-bit ADC capability to be added to any PICmicro® microcontroller. In addition, new customers will find the performance and price of the MCP300X family very attractive.

Applications for the MCP300X family include data acquisition, instrumentation and measurement, multi-channel data loggers, industrial PCs, motor control, robotics, industrial automation, smart sensors, portable instrumentation and home medical appliances.



### Features:

- 200k samples/second
- 1, 2, 4 or 8 channels
- Low Power: 5 nA typical standby, 425  $\mu$ A typical active
- $\pm 1$  LSB INL,  $\pm 1$  LSB DNL
- No missing codes
- Industrial temperature range:  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$
- Single supply operation: 2.7V to 5.5V
- SPI serial interface
- PDIP and SOIC packages

### Related Application Notes:

- AN679 Temperature Sensing Technologies
- AN684 Single Supply Temperature Sensing with Thermocouples
- AN685 Thermistors in Single Supply Temperature Sensing Circuits
- AN687 Precision Temperature Sensing with RTD Circuits
- AN699 Anti-Aliasing Analog Filters for Data Acquisition Systems

# MCP300X 10-Bit Analog-to-Digital Converters *Continued*

## Additional Information:

- Microchip's web site: [www.microchip.com](http://www.microchip.com)
- Microchip's *Technical Library CD-ROM*, Order No. DS00161
- More than 112 Application Notes available:
  - *Embedded Control Handbook*, Order No. DS00092
  - *Embedded Control Handbook, Volume 2, Math Library*, Order No. DS00167
- Microchip's *Overview, Quality Systems and Customer Interface System*, Order No. DS00169
- Third party software and hardware support:
  - Emulators
  - Programmers
  - Gang Programmers
  - Software Tools
  - Development Boards and Accessories
  - Design Consultants
  - *Third Party Guide*, Order No. DS00104

**MCP300X High-Performance 10-Bit Analog-to-Digital Converters**

| Product | Resolution (Bits) | No. of Channels | Sampling Rate (ksps) | INL ( $\pm$ LSB) | DNL ( $\pm$ LSB) | Supply Voltage | Temperature Range | Standby Current @ 5V (typical, $\mu$ A) | Operating Current @ 5V (typical, $\mu$ A) | Packages           |
|---------|-------------------|-----------------|----------------------|------------------|------------------|----------------|-------------------|---|---|--------------------|
| MCP3001 | 10                | 1               | 200                  | 1                | 1                | 2.7 - 5.5      | -40° to +85°C     | 0.005                                   | 400                                       | 8P, 8SO, 8TSSOP    |
| MCP3002 | 10                | 2               | 200                  | 1                | 1                | 2.7 - 5.5      | -40° to +85°C     | 0.005                                   | 525                                       | 8P, 8SO, 8TSSOP    |
| MCP3004 | 10                | 4               | 200                  | 1                | 1                | 2.7 - 5.5      | -40° to +85°C     | 0.005                                   | 425                                       | 14P, 14SO, 14TSSOP |
| MCP3008 | 10                | 8               | 200                  | 1                | 1                | 2.7 - 5.5      | -40° to +85°C     | 0.005                                   | 425                                       | 16P, 16SO          |

## Development Tool Support

Microchip is offering a comprehensive set of support tools including application notes and the Analog Evaluation System. The evaluation system consists of the analog evaluation driver board, incorporating a PICmicro microcontroller, coupled with an MCP300X device-specific evaluation board. Windows®-based software features powerful data collection and analysis

### Americas

Atlanta (770) 640-0034  
 Austin-Analog (512) 345-2030  
 Boston (978) 692-3848  
 Boston-Analog (978) 371-6400  
 Chicago (630) 285-0071  
 Dallas (972) 818-7423  
 Dayton (937) 291-1654  
 Detroit (248) 538-2250  
 Los Angeles (949) 263-1888  
 Mountain View-Analog (650) 968-9241  
 New York (631) 273-5305  
 San Jose (408) 436-7950  
 Toronto (905) 673-0699

### Asia/Pacific

Australia 61 2 9868 6733  
 China-Beijing 86 10 85282100  
 China-Shanghai 86 21 6275 5700  
 Hong Kong 852 2401 1200  
 India 91 80 2290061  
 Japan 81 45 471 6166  
 Korea 82 2 554 7200  
 Singapore 65 334 8870  
 Taiwan 886 2 2717 7175

### Europe

Denmark 45 4420 9895  
 France 33 1 69 53 63 20  
 Germany 49 89 627 144 0  
 Germany-Analog 49 89 895650 0  
 Italy 39 039 65791 1  
 United Kingdom 44 118 921 5869

As of 02/01/01



Microchip Technology Inc. • 2355 W. Chandler Blvd. • Chandler, AZ 85224-6199 • (480) 792-7200 • Fax (480) 792-9210

The Microchip name, logo, PIC, PICmicro, PICMASTER, PICSTART, PRO MATE, KeeLoq, SEEVAL, MPLAB and The Embedded Control Solutions Company are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries. Total Endurance, ICSR In-Circuit Serial Programming, FilterLab, MXDEV, microID, FlexROM, fuzzyLAB, MPASM, MPLINK, MPLIB, PICDEM, ICEPIC, Migratable Memory, FanSense, ECONOMONITOR, SelectMode and microPort are trademarks and SQTP is a service mark of Microchip Technology Inc. All other trademarks mentioned herein are the property of their respective companies. Information subject to change. © 2001 Microchip Technology Inc. All rights reserved. Printed in the U.S.A. DS20044B 2/01