


Hex Inverter

The LS04 is a bipolar, NPN, sealed-junction, silicon integrated circuit. It is manufactured in low-power Schottky technology and is available in a wire-bonded, 14-pin plastic DIP or surface mount package.



Electrical Characteristics

VCC = 5.0 ±0.5 V, TA = -55 to +125°C (WA-LS)
VCC = 5.0 ±0.25 V, TA = 0 to 70°C (WP90222L3)
VCC = 5.0 ±0.5 V, TA = -40 to +85°C (WA-LSD, WP91397L3)

		WA-LS		WP, WA-LSD		
Parameter	Symbol	Min	Max	Min	Max	Units
Output Voltage, VCC = 4.5 V (WA-LS), 4.75 V (WP, WA-LSD) Low, IOL = 4.0 mA IOL = 8.0 mA High, IOH = -0.4 mA	VOL	—	0.4	—	0.4	V
	VOL	—	0.5	—	0.5	V
	VOH	2.5	—	2.7	—	V
Input Voltage, VCC = 4.5 V (WA-LS), 4.75 V (WP, WA-LSD) Low High Clamp, IIN = -18.0 mA	VIL	—	0.7	—	0.8*	V
	VIH	2.0	7.5	2.0	5.5	V
	VIK	—	-1.5	—	-1.5	V
Input Current, VCC = 5.5 V (WA-LS), 5.25 V (WP, WA-LSD) Low, VIL = 0.4 V High, VIH = 2.7 V @ VI max, VI = 7.0 V (WA-LS), 5.5 V (WP, WA-LSD)	IIL	—	-0.4	—	-0.4	mA
	IiH	—	20.0	—	20.0	µA
	Ii	—	0.1	—	0.1	mA
Output Current, VCC = 5.5 V (WA-LS), 5.25 V (WP, WA-LSD) Short-Circuit	Ios	-20.0	-100.0	-20.0	-100.0	mA
Supply Current, VCC = 5.5 V (WA-LS), 5.25 V (WP, WA-LSD) Output Low Output High	ICCL	—	6.6	—	6.6	mA
	ICCH	—	2.4	—	2.4	mA

* WA-LSD, WP91397L3: VIL = 0.7 V

Timing Characteristics

VCC = 5.0 V, TA = 25°C, CL = 15 pF

		WA-LS		WP, WA-LSD		
Parameter	Symbol	Min	Max	Min	Max	Units
Propagation Delay						
Low-to-High	tPLH	—	10.0	—	15.0	ns
High-to-Low	tPHL	—	10.0	—	15.0	ns

Maximum Ratings

Power supply voltage (VCC)	7.0 V
Operating temperature (TA)	WA-LS: -55 to +125°C WP90222L3: 0 to 70°C WA-LSD, WP91397L3: -40 to +85°C
Storage temperature (Tstg)	-65 to +150°C

Maximum ratings are defined as the limiting conditions that the user can apply to the device under all variations of circuit and environmental conditions. If any rating is exceeded, permanent damage to the device may result.

Bonding or soldering of the external leads of this device can be performed safely at temperatures up to 300°C.