




## 2W005 THRU 2W10

**SINGLE PHASE 2.0 AMPS . SILICON BRIDGE RECTIFIERS**



### FEATURES

- \* Ideal for printed circuit board
- \* High Surge Current Capability
- \* Reliable low cost construction technique results in inexpensive product


### VOLTAGE RANGE

50 to 1000 Volts

CURRENT

2.0 Amperes

**WOB**



Dimensions in inches and (millimeters)

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

TYPE NUMBER	SYMBOLS	2W005	2W01	2W02	2W04	2W06	2W08	2W10	UNITS
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Bridge Input Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum D.C Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current @ $T_A = 50^\circ\text{C}$	$I_{F(AV)}$	2.0							A
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	50							A
Maximum Forward Voltage Drop per element @ 1.0A	$V_F$	1.10							V
Maximum Reverse Current at Rated @ $T_A = 25^\circ\text{C}$ D.C Blocking Voltage per element @ $T_A = 100^\circ\text{C}$	$I_R$	10 500							$\mu\text{A}$ $\mu\text{A}$
Operating Temperature Range	$T_J$	- 55 to + 125							$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	- 55 to + 150							$^\circ\text{C}$

## RATINGS AND CHARACTERISTIC CURVES (2W005 THRU 2W10)

FIG. 1-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT - PER ELEMENT




FIG. 2-TYPICAL FORWARD OUTPUT CURRENT DERATING CURVE




FIG. 3-TYPICAL FORWARD CHARACTERISTICS PER ELEMENT




FIG. 4-TYPICAL REVERSE CHARACTERISTICS PER ELEMENT

