

TD62308AP, TD62308F, TD62308AF

4CH LOW INPUT ACTIVE HIGH-CURRENT DARLINGTON SINK DRIVER


The TD62308AP/F/AF are non-inverting transistor array which are comprised of four NPN darlington output stages and PNP input stages. These devices are low level input active driver and are suitable for operation with TTL, 5V CMOS and 5V Microprocessor which have sink current output drivers. Applications include relay, hammer, lamp and stepping moter drivers.

FEATURES


- Output current (single output) 1.5A (Max.)
- High sustaining voltage output 35V (Min.) (TD62308F)
50V (Min.) (TD62308AP, TD62308AF)
- Output clamp diodes
- Input compatible with TTL and 5V CMOS
- Low level active inputs
- Standard supply voltage
- Two V_{CC} terminals V_{CC1} , V_{CC2} (separated)
- GND and SUB terminal = heat sink
- Package type-AP : DIP-16pin
- Package type-F, AF : PFP-16pin

PIN CONNECTION (TOP VIEW)


TD62308AP



TD62308F, TD62308AF




TD62308AP



DIP16-P-300-2.54A


TD62308F
TD62308AF



HSOP16-P-300-1.00

Weight
DIP16-P-300-2.54A : 1.11g (Typ.)
HSOP16-P-300-1.00 : 0.50g (Typ.)

SCHEMATICS (EACH DRIVER)



(Note) The input and output parasitic diodes cannot be used as clamp diodes.

961001EBA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The products described in this document are subject to foreign exchange and foreign trade control laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Supply Voltage		V _{CC}	- 0.5~10	V
Output Sustaining Voltage	F	V _{CE} (SUS)	- 0.5~35	V
	AP, AF		- 0.5~50	
Output Current		I _{OUT}	1.5	A / ch
Input Current		I _{IN}	- 10	mA
Input Voltage		V _{IN}	- 0.5~30	V
Clamp Diode Reverse Voltage	F	V _R	35	V
	AP, AF		50	
Clamp Diode Forward Current		I _F	1.5	A
Power Dissipation	AP	P _D	1.47 / 2.7 (Note 1)	W
	F, AF		0.9 / 1.4 (Note 2)	
Operating Temperature		T _{opr}	- 40~85	°C
Storage Temperature		T _{stg}	- 55~150	°C

(Note 1) On Glass Epoxy (50 × 50 × 1.6mm Cu 50%)

(Note 2) On Glass Epoxy (60 × 30 × 1.6mm Cu 30%)

RECOMMENDED OPERATING CONDITIONS (Ta = - 40~85°C)

CHARACTERISTIC		SYMBOL	CONDITION		MIN.	TYP.	MAX.	UNIT
Supply Voltage		V _{CC}	—		4.5	—	5.5	V
Output Sustaining Voltage	F	V _{CE} (SUS)	—		0	—	35	V
	AP, AF		—		0	—	50	
Output Current	AP	I _{OUT}	DC 1 circuit, Ta = 25°C		0	—	1250	mA / ch
			T _{pw} = 25ms 4 circuits Ta = 85°C T _j = 120°C	Duty = 10%	0	—	1250	
	Duty = 50%			0	—	700		
	Duty = 10%			0	—	1250		
	Duty = 50%			0	—	390		
F, AF								
Input Voltage		V _{IN}	—		0	—	25	V
Input Voltage	Output On	V _{IN} (ON)	—		0	—	V _{CC} – 3.6	V
	Output Off	V _{IN} (OFF)	—		V _{CC} – 1.0	—	V _{CC}	
Clamp Diode Reverse Voltage	F	V _R	—		—	—	35	V
	AP, AF		—		—	—	50	
Clamp Diode Forward Current		I _F	—		—	—	1.25	A
Power Dissipation	AP	P _D	Ta = 85°C (Note 1)		—	—	1.4	W
	F, AF		Ta = 85°C (Note 2)		—	—	0.7	



(Note 1) On Glass Epoxy (50 × 50 × 1.6mm Cu 50%)

(Note 2) On Glass Epoxy (60 × 30 × 1.6mm Cu 30%)


ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CIR- CUIT	TEST CONDITION		MIN.	TYP.	MAX.	UNIT
Output Leakage Current	AP, AF	I _{CEX}	1	V _{CE} = 50V, Ta = 25°C		—	—	50	μA
	V _{CE} = 50V, Ta = 85°C			—	—	100			
	V _{CE} = 35V, Ta = 25°C			—	—	50			
	V _{CE} = 35V, Ta = 85°C			—	—	100			
Output Saturation Voltage		V _{CE (sat)}	3	I _{OUT} = 1.25A		—	—	1.8	V
				I _{OUT} = 0.7A		—	—	1.3	
Input Voltage	“H” Level	V _{IH}	—	—		V _{CC} - 1.6	—	25	V
	“L” Level	V _{IL}	—	—		—	—	V _{CC} - 3.6	
Input Current	“H” Level	I _{IH}	—	—		—	—	10	μA
	“L” Level	I _{IL}				—	-0.05	-0.36	mA
Clamp Diode Reverse Current	AP, AF	I _R	4	V _R = 50V, Ta = 25°C		—	—	50	μA
	F			V _R = 35V, Ta = 25°C		—	—	50	
Clamp Diode Forward Voltage		V _F	5	I _F = 1.25A		—	1.5	2.0	V
Supply Current	Output On	I _{CC (ON)}	2	V _{CC} = 5.5V, V _{IN} = 0V		—	8.5	12.5	mA / ch
	Output Off	I _{CC (OFF)}		V _{CC} = 5.5V, V _{IN} = V _{CC}		—	—	1.0	μA
Turn-On Delay	F	t _{ON}	6	C _L = 15pF	V _{OUT} = 35V R _L = 28Ω	—	0.2	—	μs
	AP, AF				V _{OUT} = 50V R _L = 40Ω				
Turn-Off Delay	F	t _{OFF}			V _{OUT} = 35V R _L = 28Ω	—	5.0	—	
	AP, AF				V _{OUT} = 35V R _L = 40Ω				


TEST CIRCUIT

1. I_{CEX} 2. I_{CC} 


3. $V_{CE}(\text{sat})$




4. I_R



5. V_F



6. t_{ON} , t_{OFF}











(Note 1) Pulse width $50\mu s$, duty cycle 10%
Output impedance 50Ω $t_r \leq 5ns$, $t_f \leq 10ns$

(Note 2) C_L includes probe and jig capacitance.

PRECAUTIONS for USING


Utmost care is necessary in the design of the output line, V_{CC} , COMMON and GND line since IC may be destroyed due to short-circuit between outputs, air contamination fault, or fault by improper grounding.





OUTLINE DRAWING
DIP16-P-300-2.54A

Unit : mm






Weight : 1.11g (Typ.)

OUTLINE DRAWING

HSOP16-P-300-1.00

Unit : mm



Weight : 0.50g (Typ.)