

TOSHIBA BIPOLAR DIGITAL INTEGRATED CIRCUIT SILICON MONOLITHIC

# TD62308BP-1, TD62308BF



## 4ch LOW INPUT ACTIVE HIGE-CURRENT DARLINGTON SINK DRIVER

The TD62308BP-1 and TD62308BF are non-inverting transistor array which are comprised of four NPN darlington output stages and PNP input stages. This device is low level input active driver and are suitable for operation with TTL, 5V CMOS and 5V Microprocessor which have sink current output drivers. Applications include relay, hammer, lamp and stepping motor drivers.


### FEATURES

- Two  $V_{CC}$  Terminals  $V_{CC1}$ ,  $V_{CC2}$  (Separated)
- Package Type BP-1 : DIP-16pin  
BF : PFP-16pin
- High Sustaining Voltage Output :  $V_{CE(SUS)} = 80V$  (Min.)
- Output Current (Single Output) :  $I_{OUT} = 1.5A$  (Max.)
- Output Clamp Diodes
- Low Level Active Input
- GND and SUB Terminal = Heat Sink
- Input Compatible with TTL and 5V CMOS
- Standard Supply Voltage

### PIN CONNECTION (TOP VIEW)




TD62308BP-1



DIP16-P-300-2.54A

TD62308BF




HSOP16-P-300-1.00

### Weight

DIP16-P-300-2.54A : 1.11g (Typ.)  
HSOP16-P-300-1.00 : 0.50g (Typ.)

### SCHEMATICS (EACH DRIVER)



(Note) The output parasitic diode cannot be used as clamp diode.

961001EBA2

• TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.

## MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Supply Voltage	V <sub>CC</sub>	7	V
Output Sustaining Voltage	V <sub>CE(SUS)</sub>	− 0.5~80	V
Parasitic Transistor Output Voltage	V <sub>CEF</sub> (*1)	80	V
Output Current	I <sub>OUT</sub>	1.5	A / ch
Input Current	I <sub>IN</sub>	− 10	mA
Input Voltage	V <sub>IN</sub>	7	V
Clamp Diode Reverse Voltage	V <sub>R</sub>	80	V
Clamp Diode Forward Current	I <sub>F</sub>	1.5	A
Power Dissipation	BP-1	P <sub>D</sub>	W
	BF		
Operating Temperature	T <sub>opr</sub>	− 40~85	°C
Storage Temperature	T <sub>stg</sub>	− 55~150	°C

(\*1) Parasitic Transistor (COMMON - GND - OUTPUT) Output Voltage

(\*2) On Glass Epoxy PCB (50 × 50 × 1.6mm Cu 50%)

(\*3) On Glass Epoxy PCB (60 × 30 × 1.6mm Cu 30%)

## RECOMMENDED OPERATING CONDITIONS (Ta = − 40~85°C)

CHARACTERISTIC	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Supply Voltage	V <sub>CC</sub>	—	4.5	—	5.0	V
Output Sustaining Voltage	V <sub>CE(SUS)</sub>	—	0	—	80	V
Output Current	I <sub>OUT</sub>	DC 1 Circuit, Ta = 25°C	0	—	1.25	A / ch
		T <sub>pw</sub> = 25ms				
		4 Circuits				
		T <sub>j</sub> = 120°C				
		Ta = 85°C				
Input Voltage	V <sub>IN</sub>	—	0	—	25	V
	Output On	V <sub>IN(ON)</sub>	0	—	V <sub>CC</sub> − 3.6	V
	Output Off	V <sub>IN(OFF)</sub>	V <sub>CC</sub> − 1.0	—	V <sub>CC</sub>	
Clamp Diode Reverse Voltage	V <sub>R</sub>	—	—	—	80	V
Clamp Diode Forward Current	I <sub>F</sub>	—	—	—	1.25	A
Power Dissipation	BP-1	P <sub>D</sub>	—	—	1.4	W
	BF				0.7	

(\*1) On Glass Epoxy PCB (50 × 50 × 1.6mm Cu 50%)

(\*2) On Glass Epoxy PCB (60 × 30 × 1.6mm Cu 30%)





961001EBA2'

- The products described in this document are subject to foreign exchange and foreign trade control laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.


## ELECTRICAL CHARACTERISTICS (Ta = 25°C Unless otherwise noted)

CHARACTERISTIC		SYMBOL	TEST CIRCUIT	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Input Voltage	"H" level	$V_{IH}$	—	—	$V_{CC} - 1.6$	—	$V_{CC}$	V
	"L" level	$V_{IL}$	—	—	—	—	$V_{CC} - 3.6$	
Input Current	"H" level	$I_{IH}$	2	—	—	—	10	$\mu A$
	"L" level	$I_{IL}$	2	$V_{CC} = 5.5V, V_{IN} = 0.4V$	—	-0.05	-0.36	mA
Output Leakage Current		$I_{CEX}$	1	$V_{OUT} = 80V, Ta = 25^{\circ}C$	—	—	50	$\mu A$
				$V_{OUT} = 80V, Ta = 85^{\circ}C$	—	—	100	
Output Saturation Voltage		$V_{CE(sat)}$	3	$V_{CC} = 4.5V, I_{OUT} = 1.25A$	—	1.3	1.8	V
Clamp Diode Reverse Current		$I_R$	4	$V_R = 80V, Ta = 25^{\circ}C$	—	—	50	$\mu A$
Clamp Diode Forward Voltage		$V_F$	5	$I_F = 1.25A$	—	1.5	2.0	V
Supply Current	Output On	$I_{CC(ON)}$	2	$V_{CC} = 5.5V, V_{IN} = 0V$	—	8.5	12.5	mA / ch
	Output Off	$I_{CC(OFF)}$	2	$V_{CC} = 5.5V, V_{IN} = V_{CC}$	—	—	10	$\mu A$
Turn-On Delay		$t_{ON}$	6	$V_{OUT} = 80V, R_L = 68\Omega$	—	0.2	—	$\mu s$
Turn-Off Delay		$t_{OFF}$			—	5.0	—	
Parasitic Transistor Output Voltage		$V_{CEF}$	7	$I_{CEF} = 150mA$	80	—	—	V


## TEST CIRCUIT

1.  $I_{CEX}$ 2.  $I_{CC}, I_{IN}$ 3.  $V_{CE(sat)}$ 4.  $I_R$ 

5.  $V_F$




6.  $t_{ON}$ ,  $t_{OFF}$



(Note 1) Pulse Width  $50\mu s$ , Duty Cycle 10%、  
Output Impedance  $50\Omega$ ,  $t_r \leq 5ns$ ,  $t_f \leq 10ns$







(Note 2)  $C_L$  includes probe and jig capacitance



7.  $V_{cef}$



**PRECAUTIONS for USING**


Utmost care is necessary in the design of the output line,  $V_{CC}$ , COMMON and GND line since IC may be destroyed due to short-circuit between outputs, air contamination fault, or fault by improper grounding.





OUTLINE DRAWING  
DIP16-P-300-2.54A

Unit : mm






Weight : 1.11g (Typ.)

**OUTLINE DRAWING**

HSOP16-P-300-1.00

Unit : mm



Weight : 0.50g (Typ.)