

**Specification Status: Released**



**Maximum Electrical Rating**

**Voltage: 16V<sub>DC</sub>**  
**Short Circuit Current: 20A**

**Notes:**

1. All terminations are tin plated.
2. Drawing not to scale

**Marking:**



**TABLE I. DIMENSIONS:**

|     | A       |         | B       |         | C       |         | D       |         | E       |
|-----|---------|---------|---------|---------|---------|---------|---------|---------|---------|
|     | MIN     | MAX     | MIN     | MAX     | MIN     | MAX     | MIN     | MAX     | MIN     |
| mm: | 3.00    | 3.40    | 0.58    | 0.82    | 1.37    | 1.80    | 0.25    | 0.75    | 0.076   |
| in: | (0.118) | (0.134) | (0.023) | (0.032) | (0.054) | (0.071) | (0.010) | (0.030) | (0.003) |

**TABLE II. PERFORMANCE RATINGS:**

| CURRENT RATINGS** |      |                 |      |                 |      | TIME TO TRIP**            | RESISTANCE VALUES |      | TRIPPED-STATE POWER DISSIPATION** |
|-------------------|------|-----------------|------|-----------------|------|---------------------------|-------------------|------|-----------------------------------|
| AMPERES AT 0°C    |      | AMPERES AT 25°C |      | AMPERES AT 60°C |      | SECONDS AT 25°C, 3.5A MAX | OHMS AT 25°C      |      | WATTS AT 25°C, 16V MAX            |
| HOLD              | TRIP | HOLD            | TRIP | HOLD            | TRIP |                           | MIN               | MAX* |                                   |
| 0.44              | 0.90 | 0.35            | 0.75 | 0.24            | 0.58 | 0.1                       | 0.45              | 1.35 | 0.6                               |

\*Maximum resistance is measured 1 hour after reflow.

\*\* Values specified were determined using PCB's with 0.030"X1.5 ounce copper traces.

Agency Recognitions:  
Reference Documents:  
Precedence:  
Effectivity:  
CAUTION:

UL, CSA, TÜV  
PS300  
This specification takes precedence over documents referenced herein.  
Reference documents shall be the issue in effect on the date of invitation for bid.  
Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

**Materials Information**

**ROHS Compliant**

Directive 2002/95/EC  
Compliant

**ELV Compliant**

Directive 2000/53/EC  
Compliant

**Pb-Free**



**Halogen Free\***



\* Halogen Free refers to: Br≤900ppm, Cl≤900ppm, Br+Cl≤1500ppm