


PRODUCT SPECIFICATION

DATE: 08/10/01'


COSMO ELECTRONICS CORPORATION	REED RELAY: S1A120098	NO. 50R05014	REV.
		SHEET 1 OF 2	3

1. OUTSIDE DIMENSION : UNIT (mm)



TOLERANCE : $\pm 0.1\text{mm}$

2. SCHEMATIC : TOP VIEW



ISSUE Dear. ju. 08-10-01	CHECK <i>[Signature]</i> 08-10-01	APPROVED <i>[Signature]</i> 08-10-01
--------------------------------	---	--

PRODUCT SPECIFICATION

DATE: 08/10/01'

COSMO ELECTRONICS CORPORATION	REED RELAY:	NO. 50R05014	REV.
	S1A120098	SHEET 2 OF 2	3

3.0 COIL RATINGS: (AT 20°C)

3.1 Coil resistance	2000	Ω	($\pm 10\%$)
3.2 Nominal coil current	12	VDC	
3.3 Maximum Continuous voltage	20	VDC	
3.4 Must operate	8	VDC	
3.5 Must release	1.2	VDC	
3.6 Rated current	6	mA	

4.0 ELECTRONICAL CHARACTERISTICS:

4.1 Contact resistance	100	m Ω	(max)
4.2 Operate time	0.5	ms	(max)
4.3 Bounce time	0.5	ms	(max)
4.4 Release time	0.2	ms	(max)
4.5 Insulation resistance (100 VDC open contact)	10^{11}	Ω	(min)
4.6 Power	10	VA	(max)
4.7 Switching voltage	200	VDC	(max)
4.8 Switching current	0.5	A	(max)
4.9 Carry current	1.0	A	(max)
4.10 Breakdown voltage (across open contact)	250	VDC	(min)
(between coil & contact)	1000	VDC	(min)
4.11 Life expectancy (signal level)	10^8		
4.12 Operating temp	-40 to 85°C		
4.13 Storage temp	-40 to 125°C		
4.14 Resonant frequency	3.5	KHZ	
4.15 Vibration (10-2000HZ)	20	g	(max)
4.16 Minimum permissible load	100	mVDC	10uA