

# SN54AHCT244, SN74AHCT244 OCTAL BUFFERS/DRIVERS WITH 3-STATE OUTPUTS

SCLS228L – OCTOBER 1995 – REVISED JULY 2003

- Inputs Are TTL-Voltage Compatible
- Latch-Up Performance Exceeds 250 mA Per JESD 17


## description/ordering information

These octal buffers/drivers are designed specifically to improve both the performance and density of 3-state memory-address drivers, clock drivers, and bus-oriented receivers and transmitters.


The 'AHCT244 devices are organized as two 4-bit buffers/line drivers with separate output-enable ( $\overline{OE}$ ) inputs. When  $\overline{OE}$  is low, the device passes data from the A inputs to the Y outputs. When  $\overline{OE}$  is high, the outputs are in the high-impedance state.

To ensure the high-impedance state during power up or power down,  $\overline{OE}$  should be tied to  $V_{CC}$  through a pullup resistor; the minimum value of the resistor is determined by the current-sinking capability of the driver.

SN54AHCT244 . . . J OR W PACKAGE  
SN74AHCT244 . . . DB, DGV, DW, N, NS, OR PW PACKAGE  
(TOP VIEW)



SN54AHCT244 . . . FK PACKAGE  
(TOP VIEW)



## ORDERING INFORMATION

| T <sub>A</sub> | PACKAGE†    |               | ORDERABLE PART NUMBER | TOP-SIDE MARKING |
|----------------|-------------|---------------|-----------------------|------------------|
| –40°C to 85°C  | PDIP – N    | Tube          | SN74AHCT244N          | SN74AHCT244N     |
|                | SOIC – DW   | Tube          | SN74AHCT244DW         | AHCT244          |
|                |             | Tape and reel | SN74AHCT244DWR        |                  |
|                | SOP – NS    | Tape and reel | SN74AHCT244NSR        | AHCT244          |
|                | SSOP – DB   | Tape and reel | SN74AHCT244DBR        | HB244            |
|                | TSSOP – PW  | Tube          | SN74AHCT244PW         | HB244            |
|                |             | Tape and reel | SN74AHCT244PWR        |                  |
| –55°C to 125°C | TVSOP – DGV | Tape and reel | SN74AHCT244DGVR       | HB244            |
|                | CDIP – J    | Tube          | SNJ54AHCT244J         | SNJ54AHCT244J    |
|                | CFP – W     | Tube          | SNJ54AHCT244W         | SNJ54AHCT244W    |
|                | LCCC – FK   | Tube          | SNJ54AHCT244FK        | SNJ54AHCT244FK   |

† Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at [www.ti.com/sc/package](http://www.ti.com/sc/package).



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS  
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 2003, Texas Instruments Incorporated  
On products compliant to MIL-PRF-38535, all parameters are tested unless otherwise noted. On all other products, production processing does not necessarily include testing of all parameters.

# SN54AHCT244, SN74AHCT244

## OCTAL BUFFERS/DRIVERS


### WITH 3-STATE OUTPUTS

SCLS228L – OCTOBER 1995 – REVISED JULY 2003

FUNCTION TABLE  
(each 4-bit buffer/driver)

| INPUTS          |   | OUTPUT |
|-----------------|---|--------|
| $\overline{OE}$ | A | Y      |
| L               | H | H      |
| L               | L | L      |
| H               | X | Z      |

#### logic diagram (positive logic)



#### absolute maximum ratings over operating free-air temperature range (unless otherwise noted)<sup>†</sup>

|                                                                |                            |
|----------------------------------------------------------------|----------------------------|
| Supply voltage range, $V_{CC}$                                 | –0.5 V to 7 V              |
| Input voltage range, $V_I$ (see Note 1)                        | –0.5 V to 7 V              |
| Output voltage range, $V_O$ (see Note 1)                       | –0.5 V to $V_{CC} + 0.5$ V |
| Input clamp current, $I_{IK}$ ( $V_I < 0$ )                    | –20 mA                     |
| Output clamp current, $I_{OK}$ ( $V_O < 0$ or $V_O > V_{CC}$ ) | ±20 mA                     |
| Continuous output current, $I_O$ ( $V_O = 0$ to $V_{CC}$ )     | ±25 mA                     |
| Continuous current through $V_{CC}$ or GND                     | ±75 mA                     |
| Package thermal impedance, $\theta_{JA}$ (see Note 2):         |                            |
| DB package                                                     | 70°C/W                     |
| DGV package                                                    | 92°C/W                     |
| DW package                                                     | 58°C/W                     |
| N package                                                      | 69°C/W                     |
| NS package                                                     | 60°C/W                     |
| PW package                                                     | 83°C/W                     |
| Storage temperature range, $T_{stg}$                           | –65°C to 150°C             |

<sup>†</sup> Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

2. The package thermal impedance is calculated in accordance with JESD 51-7.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

# SN54AHCT244, SN74AHCT244 OCTAL BUFFERS/DRIVERS WITH 3-STATE OUTPUTS

SCLS228L – OCTOBER 1995 – REVISED JULY 2003

## recommended operating conditions (see Note 3)

|          |                                | SN54AHCT244 |          | SN74AHCT244 |          | UNIT |
|----------|--------------------------------|-------------|----------|-------------|----------|------|
|          |                                | MIN         | MAX      | MIN         | MAX      |      |
| $V_{CC}$ | Supply voltage                 | 4.5         | 5.5      | 4.5         | 5.5      | V    |
| $V_{IH}$ | High-level input voltage       | 2           |          | 2           |          | V    |
| $V_{IL}$ | Low-level input voltage        |             | 0.8      |             | 0.8      | V    |
| $V_I$    | Input voltage                  | 0           | 5.5      | 0           | 5.5      | V    |
| $V_O$    | Output voltage                 | 0           | $V_{CC}$ | 0           | $V_{CC}$ | V    |
| $I_{OH}$ | High-level output current      |             | –8       |             | –8       | mA   |
| $I_{OL}$ | Low-level output current       |             | 8        |             | 8        | mA   |
| $T_A$    | Operating free-air temperature | –55         | 125      | –40         | 85       | °C   |

NOTE 3: All unused inputs of the device must be held at  $V_{CC}$  or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number SCBA004.

## electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER               | TEST CONDITIONS                                        | $V_{CC}$     | $T_A = 25^\circ\text{C}$ |     |            | SN54AHCT244 |           | SN74AHCT244 |           | UNIT          |
|-------------------------|--------------------------------------------------------|--------------|--------------------------|-----|------------|-------------|-----------|-------------|-----------|---------------|
|                         |                                                        |              | MIN                      | TYP | MAX        | MIN         | MAX       | MIN         | MAX       |               |
| $V_{OH}$                | $I_{OH} = -50\ \mu\text{A}$                            | 4.5 V        | 4.4                      | 4.5 |            | 4.4         |           | 4.4         |           | V             |
|                         | $I_{OH} = -8\ \text{mA}$                               |              | 3.94                     |     |            | 3.8         |           | 3.8         |           |               |
| $V_{OL}$                | $I_{OL} = 50\ \mu\text{A}$                             | 4.5 V        |                          |     | 0.1        |             | 0.1       |             |           | V             |
|                         | $I_{OL} = 8\ \text{mA}$                                |              |                          |     | 0.36       |             | 0.44      |             | 0.44      |               |
| $I_{OZ}$                | $V_O = V_{CC}$ or GND                                  | 5.5 V        |                          |     | $\pm 0.25$ |             | $\pm 2.5$ |             | $\pm 2.5$ | $\mu\text{A}$ |
| $I_I$                   | $V_I = 5.5\ \text{V}$ or GND                           | 0 V to 5.5 V |                          |     | $\pm 0.1$  |             | $\pm 1^*$ |             | $\pm 1$   | $\mu\text{A}$ |
| $I_{CC}$                | $V_I = V_{CC}$ or GND, $I_O = 0$                       | 5.5 V        |                          |     | 4          |             | 40        |             | 40        | $\mu\text{A}$ |
| $\Delta I_{CC}^\dagger$ | One input at 3.4 V,<br>Other inputs at $V_{CC}$ or GND | 5.5 V        |                          |     | 1.35       |             | 1.5       |             | 1.5       | mA            |
| $C_i$                   | $V_I = V_{CC}$ or GND                                  | 5 V          |                          | 2.5 | 10         |             |           |             | 10        | pF            |
| $C_o$                   | $V_O = V_{CC}$ or GND                                  | 5 V          |                          | 3   |            |             |           |             |           | pF            |

\* On products compliant to MIL-PRF-38535, this parameter is not production tested at  $V_{CC} = 0\ \text{V}$ .

† This is the increase in supply current for each input at one of the specified TTL voltage levels, rather than 0 V or  $V_{CC}$ .

# SN54AHCT244, SN74AHCT244

## OCTAL BUFFERS/DRIVERS

### WITH 3-STATE OUTPUTS

SCLS228L – OCTOBER 1995 – REVISED JULY 2003

switching characteristics over recommended operating free-air temperature range,  
 $V_{CC} = 5\text{ V} \pm 0.5\text{ V}$  (unless otherwise noted) (see Figure 1)

| PARAMETER   | FROM<br>(INPUT) | TO<br>(OUTPUT) | LOAD<br>CAPACITANCE  | $T_A = 25^\circ\text{C}$ |       |     | SN54AHCT244 |      | SN74AHCT244 |     | UNIT |
|-------------|-----------------|----------------|----------------------|--------------------------|-------|-----|-------------|------|-------------|-----|------|
|             |                 |                |                      | MIN                      | TYP   | MAX | MIN         | MAX  | MIN         | MAX |      |
| $t_{PLH}$   | A               | Y              | $C_L = 15\text{ pF}$ | 5.4*                     | 7.4*  |     | 1*          | 8.5* | 1           | 8.5 | ns   |
| $t_{PHL}$   |                 |                |                      | 5.4*                     | 7.4*  |     | 1*          | 8.5* | 1           | 8.5 |      |
| $t_{PZH}$   | $\overline{OE}$ | Y              | $C_L = 15\text{ pF}$ | 7.7*                     | 10.4* |     | 1*          | 12*  | 1           | 12  | ns   |
| $t_{PZL}$   |                 |                |                      | 7.7*                     | 10.4* |     | 1*          | 12*  | 1           | 12  |      |
| $t_{PHZ}$   | $\overline{OE}$ | Y              | $C_L = 15\text{ pF}$ | 5*                       | 9.4*  |     | 1*          | 10*  | 1           | 10  | ns   |
| $t_{PLZ}$   |                 |                |                      | 5*                       | 9.4*  |     | 1*          | 10*  | 1           | 10  |      |
| $t_{PLH}$   | A               | Y              | $C_L = 50\text{ pF}$ | 5.9                      | 8.4   |     | 1           | 9.5  | 1           | 9.5 | ns   |
| $t_{PHL}$   |                 |                |                      | 5.9                      | 8.4   |     | 1           | 9.5  | 1           | 9.5 |      |
| $t_{PZH}$   | $\overline{OE}$ | Y              | $C_L = 50\text{ pF}$ | 8.2                      | 11.4  |     | 1           | 13   | 1           | 13  | ns   |
| $t_{PZL}$   |                 |                |                      | 8.2                      | 11.4  |     | 1           | 13   | 1           | 13  |      |
| $t_{PHZ}$   | $\overline{OE}$ | Y              | $C_L = 50\text{ pF}$ | 8.8                      | 11.4  |     | 1           | 13   | 1           | 13  | ns   |
| $t_{PLZ}$   |                 |                |                      | 8.8                      | 11.4  |     | 1           | 13   | 1           | 13  |      |
| $t_{sk(o)}$ |                 |                | $C_L = 50\text{ pF}$ |                          |       | 1** |             |      |             | 1   | ns   |

\* On products compliant to MIL-PRF-38535, this parameter is not production tested.

\*\* On products compliant to MIL-PRF-38535, this parameter does not apply.

noise characteristics,  $V_{CC} = 5\text{ V}$ ,  $C_L = 50\text{ pF}$ ,  $T_A = 25^\circ\text{C}$  (see Note 4)

| PARAMETER                                          | SN74AHCT244 |     |     | UNIT |
|----------------------------------------------------|-------------|-----|-----|------|
|                                                    | MIN         | TYP | MAX |      |
| $V_{OH(V)}$ Quiet output, minimum dynamic $V_{OH}$ |             | 4.1 |     | V    |
| $V_{IH(D)}$ High-level dynamic input voltage       |             | 2   |     | V    |
| $V_{IL(D)}$ Low-level dynamic input voltage        |             |     | 0.8 | V    |


NOTE 4: Characteristics are for surface-mount packages only.

operating characteristics,  $V_{CC} = 5\text{ V}$ ,  $T_A = 25^\circ\text{C}$

| PARAMETER                              | TEST CONDITIONS             | TYP | UNIT |
|----------------------------------------|-----------------------------|-----|------|
| $C_{pd}$ Power dissipation capacitance | No load, $f = 1\text{ MHz}$ | 8.2 | pF   |



## PARAMETER MEASUREMENT INFORMATION




- NOTES: A.  $C_L$  includes probe and jig capacitance.
- B. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.
- C. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 1\text{ MHz}$ ,  $Z_O = 50\ \Omega$ ,  $t_r \leq 3\text{ ns}$ ,  $t_f \leq 3\text{ ns}$ .
- D. The outputs are measured one at a time with one input transition per measurement.
- E. All parameters and waveforms are not applicable to all devices.

Figure 1. Load Circuit and Voltage Waveforms


J (R-GDIP-T\*\*)

14 LEADS SHOWN

# CERAMIC DUAL IN-LINE PACKAGE



| PINS **<br>DIM | 14                     | 16                     | 18                     | 20                     |
|----------------|------------------------|------------------------|------------------------|------------------------|
| A              | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC |
| B MAX          | 0.785<br>(19,94)       | .840<br>(21,34)        | 0.960<br>(24,38)       | 1.060<br>(26,92)       |
| B MIN          | —                      | —                      | —                      | —                      |
| C MAX          | 0.300<br>(7,62)        | 0.300<br>(7,62)        | 0.310<br>(7,87)        | 0.300<br>(7,62)        |
| C MIN          | 0.245<br>(6,22)        | 0.245<br>(6,22)        | 0.220<br>(5,59)        | 0.245<br>(6,22)        |




4040083/F 03/03

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. This package is hermetically sealed with a ceramic lid using glass frit.
  - D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
  - E. Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.

## W (R-GDFP-F20)

## CERAMIC DUAL FLATPACK




- NOTES:
- All linear dimensions are in inches (millimeters).
  - This drawing is subject to change without notice.
  - This package can be hermetically sealed with a ceramic lid using glass frit.
  - Index point is provided on cap for terminal identification only.
  - Falls within Mil-Std 1835 GDFP2-F20

FK (S-CQCC-N\*\*)

LEADLESS CERAMIC CHIP CARRIER

28 TERMINAL SHOWN




- NOTES:
- All linear dimensions are in inches (millimeters).
  - This drawing is subject to change without notice.
  - This package can be hermetically sealed with a metal lid.
  - The terminals are gold plated.
  - Falls within JEDEC MS-004



## N (R-PDIP-T\*\*)

16 PINS SHOWN

## PLASTIC DUAL-IN-LINE PACKAGE



NOTES: A. All linear dimensions are in inches (millimeters).

B. This drawing is subject to change without notice.


C Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).

D The 20 pin end lead shoulder width is a vendor option, either half or full width.

## DGV (R-PDSO-G\*\*)

## PLASTIC SMALL-OUTLINE

24 PINS SHOWN




- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15 per side.  
 D. Falls within JEDEC: 24/48 Pins – MO-153  
 14/16/20/56 Pins – MO-194

## DW (R-PDSO-G\*\*)

## PLASTIC SMALL-OUTLINE PACKAGE

16 PINS SHOWN




- NOTES: A. All linear dimensions are in inches (millimeters).  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).  
 D. Falls within JEDEC MS-013

# MECHANICAL DATA

NS (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

14-PINS SHOWN



| DIM \ PINS ** | 14    | 16    | 20    | 24    |
|---------------|-------|-------|-------|-------|
| A MAX         | 10,50 | 10,50 | 12,90 | 15,30 |
| A MIN         | 9,90  | 9,90  | 12,30 | 14,70 |


4040062/C 03/03

- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

DB (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE

28 PINS SHOWN




- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.  
 D. Falls within JEDEC MO-150

## PW (R-PDSO-G\*\*)

## PLASTIC SMALL-OUTLINE PACKAGE

14 PINS SHOWN



- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.  
 D. Falls within JEDEC MO-153

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

| <b>Products</b>  |                                                                    | <b>Applications</b> |                                                                          |
|------------------|--------------------------------------------------------------------|---------------------|--------------------------------------------------------------------------|
| Amplifiers       | <a href="http://amplifier.ti.com">amplifier.ti.com</a>             | Audio               | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                   |
| Data Converters  | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>     | Automotive          | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>         |
| DSP              | <a href="http://dsp.ti.com">dsp.ti.com</a>                         | Broadband           | <a href="http://www.ti.com/broadband">www.ti.com/broadband</a>           |
| Interface        | <a href="http://interface.ti.com">interface.ti.com</a>             | Digital Control     | <a href="http://www.ti.com/digitalcontrol">www.ti.com/digitalcontrol</a> |
| Logic            | <a href="http://logic.ti.com">logic.ti.com</a>                     | Military            | <a href="http://www.ti.com/military">www.ti.com/military</a>             |
| Power Mgmt       | <a href="http://power.ti.com">power.ti.com</a>                     | Optical Networking  | <a href="http://www.ti.com/opticalnetwork">www.ti.com/opticalnetwork</a> |
| Microcontrollers | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a> | Security            | <a href="http://www.ti.com/security">www.ti.com/security</a>             |
|                  |                                                                    | Telephony           | <a href="http://www.ti.com/telephony">www.ti.com/telephony</a>           |
|                  |                                                                    | Video & Imaging     | <a href="http://www.ti.com/video">www.ti.com/video</a>                   |
|                  |                                                                    | Wireless            | <a href="http://www.ti.com/wireless">www.ti.com/wireless</a>             |

Mailing Address: Texas Instruments  
Post Office Box 655303 Dallas, Texas 75265

Copyright © 2003, Texas Instruments Incorporated