

规格特性

SPECIFICATIONS

WLCB3216 TYPE

Pare Number	Impedance (Ohm)	Test Frequency (MHz)	Rated Current (mA)Max.	DCR (Ω)Max.
WLCB3216 - 0 Ω	2~5	100	500	0.20
WLCB3216 - 10 Ω	10 \pm 25%	100	500	0.20
WLCB3216 - 30 Ω	30 \pm 25%	100	500	0.20
WLCB3216 - 60 Ω	60 \pm 25%	100	500	0.20
WLCB3216 - 80 Ω	80 \pm 25%	100	500	0.20
WLCB3216 - 100 Ω	100 \pm 25%	100	900	0.15
WLCB3216 - 120 Ω	120 \pm 25%	100	900	0.15
WLCB3216 - 150 Ω	150 \pm 25%	100	900	0.15
WLCB3216 - 220 Ω	220 \pm 25%	100	700	0.35
WLCB3216 - 300 Ω	300 \pm 25%	100	700	0.35
WLCB3216 - 470 Ω	470 \pm 25%	100	400	0.35
WLCB3216 - 600 Ω	600 \pm 25%	100	400	0.40
WLCB3216 - 1000 Ω	1000 \pm 25%	100	300	0.60
WLCB3216 - 1500 Ω	1500 \pm 25%	100	300	0.70
WLCB3216 - 2000 Ω	2000 \pm 25%	100	300	0.70

规格特性

SPECIFICATIONS

WLCB2012 TYPE

Pare Number	Impedance (Ohm)	Test Frequency (MHz)	Rated Current (mA)Max.	DCR (Ω)Max.
WLCB2012 - 0 Ω	2~5	100	900	0.10
WLCB2012 - 10 Ω	10 \pm 25%	100	900	0.10
WLCB2012 - 30 Ω	30 \pm 25%	100	900	0.10
WLCB2012 - 60 Ω	60 \pm 25%	100	900	0.10
WLCB2012 - 80 Ω	80 \pm 25%	100	800	0.10
WLCB2012 - 100 Ω	100 \pm 25%	100	700	0.20
WLCB2012 - 120 Ω	120 \pm 25%	100	700	0.20
WLCB2012 - 150 Ω	150 \pm 25%	100	700	0.20
WLCB2012 - 220 Ω	220 \pm 25%	100	650	0.30
WLCB2012 - 300 Ω	300 \pm 25%	100	600	0.30
WLCB2012 - 470 Ω	470 \pm 25%	100	500	0.35
WLCB2012 - 600 Ω	600 \pm 25%	100	450	0.40
WLCB2012 - 1000 Ω	1000 \pm 25%	100	400	0.45
WLCB2012 - 1500 Ω	1500 \pm 25%	100	350	0.50
WLCB2012 - 2000 Ω	2000 \pm 25%	100	250	0.60

规格特性

SPECIFICATIONS

WLCB1608 TYPE

Pare Number	Impedance (Ohm)	Test Frequency (MHz)	Rated Current (mA)Max.	DCR (Ω)Max.
WLCB1608 - 0 Ω	2~5	100	700	0.20
WLCB1608 - 10 Ω	10 \pm 25%	100	700	0.20
WLCB1608 - 30 Ω	30 \pm 25%	100	700	0.20
WLCB1608 - 60 Ω	60 \pm 25%	100	700	0.20
WLCB1608 - 80 Ω	80 \pm 25%	100	700	0.20
WLCB1608 - 100 Ω	100 \pm 25%	100	600	0.25
WLCB1608 - 120 Ω	120 \pm 25%	100	600	0.25
WLCB1608 - 150 Ω	150 \pm 25%	100	600	0.25
WLCB1608 - 220 Ω	220 \pm 25%	100	550	0.30
WLCB1608 - 300 Ω	300 \pm 25%	100	500	0.35
WLCB1608 - 470 Ω	470 \pm 25%	100	500	0.50
WLCB1608 - 600 Ω	600 \pm 25%	100	300	0.60
WLCB1608 - 1000 Ω	1000 \pm 25%	100	200	0.70
WLCB1608 - 1500 Ω	1500 \pm 25%	100	200	1.00
WLCB1608 - 2000 Ω	2000 \pm 25%	100	150	1.20

规格特性

SPECIFICATIONS

WLCB1005 TYPE

Pare Number	Impedance (Ohm)	Test Frequency (MHz)	Rated Current (mA)Max.	DCR (Ω)Max.
WLCB1005 - 0 Ω	2~5	100	300	0.20
WLCB1005 - 10 Ω	10 \pm 25%	100	300	0.20
WLCB1005 - 30 Ω	30 \pm 25%	100	300	0.20
WLCB1005 - 60 Ω	60 \pm 25%	100	300	0.25
WLCB1005 - 80 Ω	80 \pm 25%	100	300	0.25
WLCB1005 - 100 Ω	100 \pm 25%	100	100	0.30
WLCB1005 - 120 Ω	120 \pm 25%	100	100	0.30
WLCB1005 - 150 Ω	150 \pm 25%	100	100	0.30
WLCB1005 - 220 Ω	220 \pm 25%	100	100	0.40
WLCB1005 - 300 Ω	300 \pm 25%	100	100	0.50
WLCB1005 - 470 Ω	470 \pm 25%	100	100	0.65
WLCB1005 - 600 Ω	600 \pm 25%	100	80	0.80
WLCB1005 - 1000 Ω	1000 \pm 25%	100	80	0.85