

IGBT MODULE (P-Series)


■ Features

- Square SC SOA at $10 \times I_C$
- Simplified Parallel Connection
- Narrow Distribution of Characteristics
- High Short Circuit Withstand-Capability

■ Applications

- High Power Switching
- A.C. Motor Controls
- D.C. Motor Controls
- Uninterruptible Power Supply

■ Outline Drawing




■ Maximum Ratings and Characteristics

• Absolute Maximum Ratings ($T_c=25^\circ\text{C}$)

Items	Symbols	Ratings	Units
Collector-Emitter Voltage	V_{CES}	1400	V
Gate -Emitter Voltage	V_{GES}	± 20	V
Collector Current	Continuous $T_C=25^\circ\text{C}$	I_C	200
		I_C	150
	1ms $T_C=80^\circ\text{C}$	I_C PULSE	400
		I_C PULSE	300
		$-I_C$ PULSE	150
Max. Power Dissipation	P_C	1100	W
Operating Temperature	T_j	+150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-40 ~ +125	$^\circ\text{C}$
Isolation Voltage	A.C. 1min. V_{is}	2500	V
Screw Torque	Mounting *1	3.5	Nm
	Terminals *2	3.5	

Note: *1:Recommendable Value; 2.5 - 3.5 Nm (M5)

■ Equivalent Circuit















• Electrical Characteristics (at $T_j=25^\circ\text{C}$)



Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Zero Gate Voltage Collector Current	I_{CES}	$V_{GE}=0V$ $V_{CE}=1400V$			2.0	mA
Gate-Emitter Leakage Current	I_{GES}	$V_{CE}=0V$ $V_{GE}=\pm 20V$			400	μA
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	$V_{GE}=20V$ $I_C=150\text{mA}$	6.0	8.0	9.0	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$T_j=25^\circ\text{C}$ $V_{GE}=15V$ $I_C=150A$		2.7	3.0	V
		$T_j=125^\circ\text{C}$ $V_{GE}=15V$ $I_C=150A$		3.3		
Input capacitance	C_{ies}	$V_{GE}=0V$		15000		pF
Output capacitance	C_{oes}	$V_{CE}=10V$		2000		
Reverse Transfer capacitance	C_{res}	$f=1\text{MHz}$		1000		
Turn-on Time	t_{ON}	$V_{CC}=600V$ $I_C=150A$			1.2	μs
					0.6	
Turn-off Time	t_{OFF}	$V_{GE}=\pm 15V$ $R_G=5.6\Omega$			1.0	
					0.3	
Diode Forward On-Voltage	V_F	$I_F=150A$ $V_{GE}=0V$		2.4	3.3	V
Reverse Recovery Time	t_{rr}	$I_F=150A$			350	ns

• Thermal Characteristics

Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance	$R_{th(j-c)}$	IGBT			0.11	$^\circ\text{C/W}$
	$R_{th(j-e)}$	Diode			0.24	
	$R_{th(c-f)}$	With Thermal Compound		0.025		







以上产品全新原装进口，有现货，直接代理商，有价格优势，100%全新原装

深圳市嘉林电子有限公司 欧阳 13502822457 0755-25981289 QQ:527328927

