



Sprinter – S12V170 data sheet



Terminal: Drawing:



Specifications:

Part numbers not valid for North America, use type for ordering!

Discharge figures are also valid for **UL 94 V0** version. Change "H" to "V" in the part number.

Example

Standard NASR120170 **H** P0FA
 UL 94 V0 NASR120170 **V** P0FA

Exide type designation	Nom. Voltage V	Power 15min 1.67 VpC 20°C W/cell	Power 15min 1.67 VpC 25°C W/cell	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Height over terminals (h2) max. mm	Weight approx. kg	Internal resistance mOhm	Short circuit current A	Terminal
S12V170	12	158	167	198	167	178	189	16.4	5.3	2341	F-M6

Constant-power discharge in W/cell @ 20 °C

Part number	Vpc	5 min	10 min	15 min	20 min	30 min	45 min	1 h	1,25 h	1,5 h
NASR120170HP0FA	1.85	236	170	136	113	85.6	63.7	50.4	41.8	36.1
NASR120170HP0FA	1.80	266	187	147	122	92.3	67.5	53.3	43.7	38.0
NASR120170HP0FA	1.75	287	198	154	127	95.2	69.4	55.2	45.6	39.0
NASR120170HP0FA	1.70	302	203	157	129	96.1	69.4	55.2	45.6	39.0
NASR120170HP0FA	1.67	307	204	158	130	97.1	70.4	55.2	45.6	39.0
NASR120170HP0FA	1.65	310	205	158	130	97.1	70.4	55.2	45.6	39.0
NASR120170HP0FA	1.60	316	207	159	131	97.1	70.4	55.2	45.6	39.0
NASR120170HP0FA	1.50	318	209	161	132	98.0	71.4	56.1	46.6	39.9