



ADLS SPLITTER-AS-GC2防雷

- SHENZHEN YIXI ELECTRONIC CO.,LTD. specialized production and sells DSL SPLITTER/POTS/FILTER
- Our product exports Uzbekistan , Australia, Turkey, the Middle East, India And so on countries and area. We may design and produce global DSL SPLITTER/POTS /FILTER.
- Conforms K 21 standards
- Independent design and production.
- Conforms ETSI the TS 101 952-1-1 V 1.1.1 standards
- Conforms UL 1950 standards
- suitable in ADSL subscriber's premises
- uses the thickened gold-plated coating material
- complete split with DSL and the POTS
- suitable in 0 - 100mA POTS loop current
- operating temperature : 15 °C to 85 °C
- Three RJ11, 1 input port (Line), 2 output ports (Phone, Modem)



specification

POST PORT IMPEDANCE

Zr: 600 Ω // 54nF

Modem impedance

30 kHz < f < 1104 kHz:
100 Ω

Nominal voice band

0.3 kHz to 3.4 kHz

Insertion loss (Zreal(1))

@ 1k Hz < 0.3dB

Delay Distortion

200Hz-4.0kHz: < 250 micro sec

DC Loop current

< 100 mA

DC resistance

< 30 Ω

Nominal voice band

0.3 kHz to 3.4 kHz

ADSL band

30 kHz to 1104 kHz

Insertion loss

300Hz--2.0kHz: > 15 dB
2.0kHz--3.4kHz: > 12dB

Stop band attenuation

25 kHz < f < 100 kHz: > 55 dB
100 kHz < f < 300 kHz: > 65 dB
300 kHz < f < 2200kHz: > 50 dB

PACKAGE:

Using carton for packing, each carton contains 370pcs
Outside box size : 220*280*400mm
Each box of net weight : 11.6KG
Each box of gross weight : 12.6KG



SHENZHEN YIXI ELECTRONICS CO.,LTD.

ADD: 3F.124 Building, ShiFeng Technology Park, Ma Shan Tou, Gongming Town, Baoan District, Shenzhen, China

TEL: +86 0755-33260038 FAX: +86 0755-33260039

<http://www.dsl-splitter.com.cn> <http://www.szvixi.com.cn>