

W&T-AD16XXX

15W 系列電源適配器

產品輸出規格

| | | | | | | | | | | | | |
|------|------|------|-------|-------|-------|-------|-------|--|--|--|--|--|
| 5.0V | 7.0V | 9.0V | 12.0V | 12.0V | 15.0V | 18.0V | 24.0V | | | | | |
| 2.0A | 2.0A | 1.5A | 1.0A | 1.5A | 1.0A | 0.8A | 0.5A | | | | | |
| 50mV | 50mV | 70mV | 100mV | 100mV | 120mV | 150mV | 150mV | | | | | |

輸入/輸出規格(INPUT/OUTPUT SPECIFICATIONS):

- 輸入電壓(INPUT VOLTAGE): 100V-240V AC, 50/60Hz
- 輸入電壓範圍(RANGE VOLTAGE): 90V-264V AC, 47-63Hz
- 輸出功率(OUTPUT POWER): 15W
- 輸出電壓(OUTPUT VOLTAGE): DC 5.0V ~ 24.0V
- 過壓保護(OVER VOLTAGE PROTECTION): 120% min
- 過流保護(OVER CURRENT PROTECTION): 120% min
- 短路保護(SHORT PROTECTION): AUTO RECOVERY
- 輸出電壓變動(LOAD REGULATION): $\pm 5\%$

常規參數(GENERAL SPECIFICATIONS):

- 工作環境溫度(OPERATING TEMPERATURE): 0 ~ 40°C
- 儲存溫度(STORAGE TEMPERATURE): -20 ~ 85°C
- 工作濕度(OPERATING RELATIVE HUMIDITY): 5 ~ 95% RH
- 耐壓(WITHSTANDING VOLTAGE): AC 3000V(min), 5ma(max).
- 絕緣阻抗(INSULATION RESISTANCE): DC 500V 100M Ω (min)

安規(SAFETY):

PSE UL CE GS EK FCC

用途(APPLICATION):

- 任何攜帶型設備或機器(ANY PORTABLE DEVICE OR MACHINE)
- 測試設備(TESTER MACHINE)
- 通訊終端設備(COMMUNICATION TERMINALS)

.....