



- NOTES:
- 1.DISPLAY TYPE: STN/YELLOW -GREEN
 - 2.VIEWING DIRECTION: 6:00
 - 3.POLARIZER MODE: TRANSPARENT/POSITIVE
 - 4.OPERATING TEMP: -10°C---+60°C
 - 5.STORAGE TEMP: -20°C---+70°C
 - 6.LCD OPERATING VOLTAGE:18.5V
 - 7.DRIVE METHOD: 1/128 DUTY 1/12BIAS
 - 8.CONTROLLER: T6963C
 - 9.BACKLIGHT: LED(YELLOW -GREEN)4.2DC(V)
 - 10.ALL UNMARKED TOLERANCES:±0.3mm
 - 11.BEZEL THICKNESS: 0.6mm) IS TO BE PAINTED BLACK

1	FG	11	DB1
2	VSS	12	DB2
3	VDD	13	DB3
4	V0	14	DB4
5	/WR	15	DB5
6	/RD	16	DB6
7	/CE	17	DB7
8	C/D	18	FS
9	RESET	19	A
10	DB0	20	K

REV.	DESCRIPTION	DATE			PC 深圳市显昌科技有限公司 SHENZHEN XIANCHANG TECHNOLOGY CO., LTD	DRAW NO. PCG240128K UNIT:mm PAGE:1/1 TOLERANCES UNLESS:±0.3	DRAWN ME CHECKED EE CHECKED APPROVED
------	-------------	------	--	--	--	--	---