



台北市 114 內湖區瑞光路 588 號 5 樓  
 Tel : 886-2-2798-6189 Fax : 886-2-2658-6184  
 E-mail : [sales@mdt.mdtic.com.tw](mailto:sales@mdt.mdtic.com.tw)

## Customer OTP Information Sheet for MDT10P72 (OTP Size: 2.0K)

1. Customer's Name : \_\_\_\_\_

2. Project Title : \_\_\_\_\_

3. Package :

Chip    MDT10P72-28K    MDT10P72-28S    MDT10P72-28SS

Note: K—SKINNY (300mil)   S—SOP (300 mil)   SS-SSOP (209 mil)

4. Options :

(a) Oscillator type----- RC    LFXT    XTAL    HFXT

(b) PRD type----- Disable    Enable

(c) OST type----- Disable(0ms)    Enable (75ms)

(d) WDT type ----- Disable    Enable

(e) PED type----- Disable    Enable

(f) A/D conversion clock----- Fosc/2    Fosc/8    Fosc/32    Frc

(g) Security----- Disable    Enable

5. Customer code :

Code from -----  Samples    File name : \_\_\_\_\_

Checksum ----- \_\_\_\_\_ H (Tool:  MDT Checksum.exe    Others: \_\_\_\_\_ )

6. Operation conditions :

Operation voltage : \_\_\_\_\_ ~ \_\_\_\_\_ V                      Operation current : \_\_\_\_\_ mA

Operation frequency : \_\_\_\_\_ Hz                      Sleep current : \_\_\_\_\_  $\mu$ A

Others :

**Note:** (1) All the Operation Conditions are referred to MDT. MDT does not guarantee with these values.

It's better for you to refer to the MDT data sheet for the guarantee values.

(2) The following mark '\*' will be filled by MDT.

\*7. MDT Serial No. : \_\_\_\_\_.

\*8. MDT checksum : \_\_\_\_\_ H

Customer : \_\_\_\_\_ Date : \_\_\_\_/\_\_\_\_/\_\_\_\_

Salesman : \_\_\_\_\_ Date : \_\_\_\_/\_\_\_\_/\_\_\_\_ , Leader: \_\_\_\_\_ Date: \_\_\_\_/\_\_\_\_/\_\_\_\_