



Size: 120mmx120mmx38mm

Weight: 540 g

Impeller: PBT UL94V-0 Reinforced Plastic

Frame: Aluminum Alloy Public Frame

Motor: Shaded Pole Induction Motor



Safety Approvals

	CE	UL	CUL	TUV
100~125	●	●	●	●
220~240	●	●	●	●

Listed Model	Bearing System	Voltage	Freq.	Current	Power	Speed	Noise	Air Flow		Static Pressure
		VAC	Hz	A	W	RPM	dBa	m3/hr	CFM	(mmH2O)
XHA12038S22H	Sleeve	220~240	50/60	0.20	23/20	2600/3000	41/44	138/158	81/93	7.0/8.8
XHA12038S22M		220~240	50/60	0.16	15/14	2400/2700	40/42	131/146	77/86	5.3/7.2
XHA12038S22L		220~240	50/60	0.10	10/9	2100/2400	36/40	112/131	66/77	3.2/5.6
XHA12038B22H	Ball	220~240	50/60	0.20	23/20	2600/3000	41/44	138/158	81/93	7.0/8.8
XHA12038B22M		220~240	50/60	0.16	15/14	2400/2700	40/42	131/146	77/86	5.3/7.2
XHA12038B22L		220~240	50/60	0.10	10/9	2100/2400	36/40	112/131	66/77	3.2/5.6
XHA12038S11H	Sleeve	100~125	50/60	0.30	23/20	2600/3000	41/44	138/158	81/93	7.0/8.8
XHA12038S11M		100~125	50/60	0.25	15/14	2400/2700	40/42	131/146	77/86	5.3/7.2
XHA12038S11L		100~125	50/60	0.20	10/9	2100/2400	36/40	112/131	66/77	3.2/5.6
XHA12038B11H	Ball	100~125	50/60	0.30	23/20	2600/3000	41/44	138/158	81/93	7.0/8.8
XHA12038B11M		100~125	50/60	0.25	15/14	2400/2700	40/42	131/146	77/86	5.3/7.2