

THERMOPILE TYPE INFRARED SENSOR

A-PDF Split DEMO : Purchase from www.A-PDF.com to remove the watermark

THERMOPILE

Thermopile type Infrared sensor
utilizing own silicon micromachining
technology.


Applications: Tympanic thermometer
Microwave oven
Non contact temperature measurement



Part number

Part No.	type	Thermistor
10TP583T	TO18	Built-in

Dimensions



Ratings

Parameters	Value		Unit	Conditions
	10TP581	10TP583T		
Sensitive area	1.05×1.05		mm ²	Size of Absorbing Film
*1 Responsivity	15±30%		V/W	
*1 Output Voltage	200±30%		μV	
*2 Output Voltage	1.00±30%		mV	
*1 Temperature Coefficient of Responsivity	0.02±0.02		% / °C	Reference
Thermopile Resistance	65±30%		kΩ	
Temperature Coefficient of Thermopile Resistance	±0.1		% / °C	
Johnson Noise Voltage	33		nV / √Hz	Johnson Noise r.m.s., 298K 1Hz Typical
*1 S/N Ratio	75.7		dB	Output Voltage/Johnson Noise, Typical
*1 Noise Equivalent Power	2.2		nW / Hz ^{1/2}	Typical
*1 Specific Detectivity	4.7×10 ⁷		cm·Hz ^{1/2} /w	Typical
Time Constant	15		ms	Typical
Operating Temperature range	-20~100		°C	
Storage Temperature range	-40~100		°C	
Filter Range	Cut on 5		μm	Standard
Field of View	±50		deg.	Incident Angle to Achieve 50% Responsivity
Insulation Resistance	≥ 500		MΩ	Application of DC25V
Sealing	≤ 1×10 ⁻⁹		Pa·m ³ /s	
*3 Thermistor Resistance Value	100±3%		kΩ	Rated Zero-power Resistance Value at 25°C
*3 Thermistor B-Value	3435±0.7%		K	
*3 Thermistor Rated Power	0.5		mW	at 25°C

*1 Test Condition
Blackbody Temperature : 500K
Sensor-Blackbody Distance : 100mm
Sensor Temperature : 298K
Aperture size : φ12.7mm

*2 Test Condition
Blackbody Temperature : 310K
Sensor Temperature : 298K

*3 Built-in Type