



## SPECIFICATIONS

Current Rating: 1.5AMP  
 Contact Resistance: 20mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstand Voltage: 500V AC/minute  
 Operation Temperature: -40 °C to +105 °C  
 Contact Material: Bresa  
 Contact Plating: Au or Sn over 50 μ "Ni  
 Insulator Material: Polyester (UL94V-0)

## 32X-1 XX-S 1 3 1-XXX

**Insulator Height:**  
 2=2.00mm 5=1.50mm  
**Number of Row:**  
 2=Double Row  
**Number of Position:**  
 02 ~ 80 PIN  
**Tail & Mounting Style:**  
 S = Straight DIP Type  
**Pin Length:**  
 XXX=A+H+C  
**Tiers Of Body:**  
 1=Single Tier  
**Insulator Material:**  
 1=PBT 2=ELCP 3=PA46  
**Contact Plated:**  
 0=Tim 1=Gold Flash  
 2=Gold 3u" 3=Gold 5u"  
 5=Gold 15u" 6=Gold 30u"

E	Units	mm	Scale	2:1	Drawing By	Date			<b>深圳市联益康电子有限公司</b> Htp://www.leyconn.com TEL: +86 (755) 26078616 FAX: 26070522	
D	Tolerance Unless Otherwise Specified				Vance	2004/07/12	Date	2004/07/12	Title	2.00mm PIN Header, Straight DIP Type
C					Reviewed By	Date	Date	2004/07/12	Sheet	1 of 1
B					Sandy	2004/07/12	Approval By	Date	Thirt Angle Projection	Drawing No.
A	RELEASED				ECN. NO.	07/12/04	Jon Chuo	2004/07/12	F/Name	REV
REV					Date	Angle	~	± 3°		A