



Circuits	3	4	5	6	7	8	9
Arrangement of Contact							
P.C Board Layout							
Tolerance	.X ±0.10						
	.XX ±0.05						

**SPECIFICATIONS**  
 Current Rating: 1.5AMP  
 Operation Temperature: -40°C to +105°C  
 Contact Resistance: 20mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstand Voltage: 500V AC  
 Insulator Material: Polyester (UL94V-0)  
 Standard: IPBT  
 Contact Material: Phosphor bronze  
 Contact Plating: Tin plated

Units	mm	Scale	5:1	Drawing By	Date	Date	Date	Date	Date
Tolerance Unless Otherwise Specified				Guo Z. Li	2010/03/16				
.X ~ ±0.30				Reviewed By	Date				
.XX ~ ±0.25				Sandy	2010/03/16				
.XXX ~ ±0.20				Approval By	Date				
Angle ~ ± 3°				Jon Chuo	2010/03/16				
REV	ECN. NO.	Date							

**leycom** 深圳市联益康电子有限公司  
 Http://www.leycom.com TEL:+86-755-26078616 FAX:26070522

Date	Sheet	Title	Drawing No.	REV
2010/03/16	1 of 1	MINI DIN, 90°直插		A
			F/Name	