


1.DIMENSION OUTLINE




2.MECHANICAL SPECIFICATIONS

ITEM	SPECIFICATIONS	ITEM	REMARK
Module Size(L×W×H)	80.8×35.0×12.8	mm	Reference Dimensional Outline
View Area(W×H)	60.0×18.0	mm	
Effective V/Area(W×H)	48.75×14.35	mm	
Number of Dots	122×32	—	
Dot Pitch(W×H)	0.54×0.54	mm	
Dot Size(W×H)	0.49×0.49	mm	
Weigh(Reflective/LED)	—	g	

3.ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	CONDITION	STANDARD	
			MIN	MAX
Logic Voltage	V _{DD}	Ta=25°C	-0.3V	6.0V
LCD Voltage	V _{LCD}		-0.3V	5.0V
Input Voltage	V _I		-0.3V	V _{DD} +0.3V
Operation Temperature	T _{OP}	—	-20°C	70°C
Storage Temperature	T _{ST}	—	-20°C	80°C

4.BLOCK DIAGRAM MECHANICAL



5.LED BACKLIGHT SPECIFICATIONS

ITEM	SYMBOL	TYPE	MAX	UNIT
Ta=25°C				
Forward Voltage	V _f	2.9	3.3	V
Forward Current	I _f	—	15	mA
Emission Vave Length	λ _P	—	—	nm

6.INTERFACE PIN CONNECTIONS

ITEM	SYMBOL	LEVEL	FUNCTIONS
1	VSS	0V	Power Ground
2	VDD	5or3.3V	Power Supply For Logic
3	VO	—	NC
4	RS(CS)	H/L	H:data L:command(Chip enable for serial mode)
5	R/W(SID)	H/L	H:read L:write(serial data for serial mode)
6	E(SCLK)	H.H→L	Enable singnal (Serial clock)
7-14	DB0-DB7	H/L	Data Bus
15	REST	H→L	Reset Signal
16	VEE	—	NC
17	LEDA	+5V	Power supply For LED Backlight
18	LEDK	0V	

7.ELECTRICAL CHARACTERISTICS

ITEM	SYMBOL	MIN	TYPE	MAX	UNIT
Ta=25°C					
Logic Power	V _{DD}	4.5	5	5.5	V
Input High Voltage	V _{IH}	2	—	V _{DD}	V
Input Low Voltage	V _{IL}	0	—	0.8	V
Output High Voltage	V _{OH}	2.4	—	V _{DD}	V
Output Low Voltage	V _{OL}	0	—	0.4	V
Logic Current	I _{DD}	—	—	1.5	mA
Operation Voltage For LCD	V _{DD} -V ₀	—	5	—	V

If you must give the led Power outsid zhe LCM. But zhe J1 must short. Example:

