



Laser Measurement Technology  
LMS5xx / LMS511 / Outdoor / Mid Range

LMS511-10100 PRO



**Model Name** > **LMS511-10100 PRO**  
**Part No.** > **1046135**




**At a glance**

- Powerful and efficient laser measurement sensor for ranges of up to 80 m
- Outstanding performance in adverse environmental conditions due to multi-echo technology
- IP 67 enclosure rating, built-in heater, highly compact design
- Low power consumption
- Fast signal processing
- Multiple I/Os
- Synchronization of multiple sensors possible

**Your benefits**

- Superior performance in a vast range of applications
- Smallest sensor with highest accuracy in its class
- Comprehensive range of lines and models to suit all performance and price requirements
- Fast, reliable object detection in nearly any weather conditions
- Low power consumption reduces total cost of ownership
- Best price/performance ratio in this sensor class on the market
- Fast, easy commissioning due to SOPAS software
- Self-monitoring functions increase system availability



**Features**

Field of application:	Outdoor
Version:	Mid Range
Variant:	PRO
Resolution power:	Standard Resolution
Light source:	Infrared (905 nm)
Laser class:	1 (IEC 60825-1 (2007-6)), eye-safe
Field of view:	190 °
Scanning frequency:	25 Hz/35 Hz/50 Hz/75 Hz/100 Hz
Angular resolution:	0.167 ° 0.25 ° 0.333 ° 0.5 ° 0.667 ° 1 °
Heating:	yes

Operating range:	0 m ... 80 m
Max. range with 10 % reflectivity:	40 m
Spot size:	11.9 mrad
Amount of evaluated echoes:	5
Fog correction:	yes

### Performance

---

Response time:	≥ 10 ms
Detectable object shape:	Almost any
Systematic error:	± 25 mm (1 m ... 10 m) ± 35 mm (10 m ... 20 m) ± 50 mm (20 m ... 30 m)
Statistical error:	± 6 mm (1 m ... 10 m) ± 8 mm (10 m ... 20 m) ± 14 mm (20 m ... 30 m)
Integrated application:	Field evaluation
Number of field sets:	10 fields
Simultaneous processing cases:	10

### Interfaces

---

Serial (RS-232, RS-422):	✓
Function (Serial (RS-232, RS-422)):	Host
Data transmission rate (Serial (RS-232, RS-422)):	9.6 kBaud ... 500 kBaud
Ethernet:	✓
Function (Ethernet):	Host
Data transmission rate (Ethernet):	10/100 Mbit
Protocol (Ethernet):	TCP/IP, OPC
CAN bus:	✓
Function (CAN bus):	Outputs extension
PROFIBUS:	-
PROFINET:	-
DeviceNet:	-
USB:	✓
Function (USB):	AUX
Data transmission rate (USB):	9.6 kBaud ... 500 kBaud
Switching inputs:	4 (Encoder)
Switching outputs:	6
Optical indicators:	5 LEDs (additional 7-segment display)
Remark (USB):	mini USB

### Mechanics/electronics

---

Electrical connection:	1 M12 4-pin plug-in connector
Operating voltage:	24 V DC
Power consumption:	22 W, + 43 W heating (typical)
Housing color:	gray (RAL 7032)
Enclosure rating:	IP 67 (EN 60529, Section 14.2.7)
Protection class:	III (EN 60529, Section 14.2.7)
Weight:	3.7 kg
Dimensions:	160 mm x 155 mm x 185 mm

### Ambient data

---

Object remission:	2 % ... > 1,000 % (reflectors)
Electromagnetic compatibility (EMC):	EN 61000-6-2:2005/EN 61000-6-3 (2001-10)

Vibration resistance:	EN 60068-2-6 (1995-04)
Shock resistance:	EN 60068-2-27 (1993-03)/EN 60068-2-29 (1993-04)
Ambient operating temperature:	-30 °C ... 50 °C
Storage temperature:	-30 °C ... 70 °C
Ambient light safety:	70,000 lx

## Operating range diagram

