

GE Series

◆ STANDARD RATINGS

Rated Voltage		350V(2V)													
μ F	ΦD	Φ8		Φ10		Φ12.5		Φ13		Φ16		Φ18		Φ19	
	1.0		8×12	64											
1.5				10×12	70										
1.8				10×16	78										
2.2				10×16	88										
2.8				10×16	96										
3.3				10×17	106										
4.7				10×20	132										
5.6						12×20	152								
6.8						12×20	220								
8.2								12.5×20	240						
10								12.5×20	280						
15										13×25	300				
22												16×25	350		
33												16×30	500		
47												16×35	660		
68														19×35	850

Rated Voltage		400V(2G)															
μ F	ΦD	Φ8		Φ10		Φ12		Φ12.5		Φ13		Φ16		Φ18		Φ19	
	1.0				10×12	72											
1.5				10×12	84												
1.8				10×16	90												
2.2				10×16	92												
2.8				10×16	100												
3.3				10×17	110												
4.7				10×20	130												
5.6						12×20	140										
6.8						12×20	220										
8.2								12.5×20	260								
10								12.5×20	280								
15										13×25	320						
22												16×25	430				
33												16×30	640				
47														18×35	840		
68															19×35	1000	

Rated Voltage		450V(2W)															
μ F	ΦD	Φ8		Φ10		Φ12		Φ12.5		Φ13		Φ16		Φ18		Φ22	
	1.0			60													
1.5			68														
1.8			72														
2.2		8×12	80														
2.8				10×12	90												
3.3				10×12	100												
4.7				10×16	110												
5.6				10×16	110												
6.8				10×16	120												
8.2				10×16	130												
10				10×16	280												
15				10×20													
22						12×20	450										
33								12.5×20	600								
47										13×25	600						
68												16×25	720				
100												16×30	920				
150														18×30	1200		
																22×35	1500

▲ Case Size (ΦD×L)

▲ Ripple current(mArms/105℃,100KHz)