


MET

Axial lead, Round
Series

1) Dimensions(外觀型式): (臥式圓柱型)



2) Specifications(產品特性):

- (a) Capacitance Tolerance (容量誤差) : ±10% (K) OR ±5% (J) at 1K HZ
- (b) MAX Dissipation Factor (最大損失角) : MAX 0.75% at 1K Hz 25°C
- (c) Temp Range (工作溫度範圍) : - 55°C ~ +125°C *
- (d) Insulation Resistance(絕緣值) : 5,000 MΩ x μF
10,000 MΩ Min.
- (e) Life Test (壽命測試) : 500 Hours at 85°C at 150% Rated Voltage
(印加150%的工作電壓於85°C/500小時)

3) MAX SIZE(本體最大尺寸表 L x D)

Unit : mm

W.V. CAP. (μF)	SIZE	100 VDC			250 VDC		
		D max.	L max.	∅ d	D max.	L max.	∅ d
1.0		9.0	19	0.8	10	24	0.8
2.2		11	24	0.8	12	31	0.8
3.3		14	24	0.8	14.5	31	0.8
4.7		13.5	31	0.8	17.5	31	0.8
5.6		15	31	0.8	19.5	31	0.8
6.8		16	31	0.8	16	46	0.8
8.2		17.5	31	0.8	17.5	46	0.8
10.0		19	31	0.8	19.5	46	0.8
15.0		18	46	0.8	24	46	1.0
22.0		22	46	1.0	29	46	1.0
33.0		23.5	56	1.0	30	56	1.0
47.0		29	56	1.0	36.5	56	1.0
68.0		32	56	1.0	41	61	1.0
82.0		37	56	1.0			
100.0		40	56	1.0			

ANY SPECIAL VALUE ARE ACCEPTABLE, ITS SIZE TO BE PROVIDED UPON REQUESTED
SIZE MAYBE CHANGED W/O NOTICE. SPECIAL SIZE IS ACCEPTABLE

- 如有需特殊尺寸 / 容量-請洽本公司.
- 以上為參考尺寸,如有更動不另行通知