


MER

Radial lead, Epoxy Dip Coated
Series

■ 1) Dimensions(外觀型式):
(立式沾漆型)



■ 2) Specifications(產品特性):

- (a) Capacitance Tolerance (容量誤差) : $\pm 10\%$ (K) OR $\pm 5\%$ (J) at 1K HZ
- (b) MAX Dissipation Factor (最大損失角) : MAX 0.75% at 1K Hz 25°C
- (c) Temp Range (工作溫度範圍) : $-55^{\circ}\text{C} \sim +125^{\circ}\text{C}^*$
- (d) Insulation Resistance(絕緣值) : 5,000 $M\Omega \times \mu F$
10,000 $M\Omega$ Min.
- (e) Life Test (壽命測試) : 500 Hours at 85°C at 150% Rated Voltage
(印加150%的工作電壓於85°C/500小時)

■ 3) MAX SIZE(本體最大尺寸表 W x H x T)

Unit : mm

W.V. SIZE CAP. (μF)	100 VDC					250 VDC				
	W max.	H max.	T max.	S ± 1.0	ϕd	W max.	H max.	T max.	S ± 1.0	ϕd
1.0	18	13.5	8	15.0	0.8	23	14	9	20.0	0.8
2.2	23	16	9	20.0	0.8	30	17	10	27.0	0.8
3.3	23	18	10.5	20.0	0.8	30	20	12.5	27.0	0.8
4.7	30	18	10.5	27.0	0.8	30	24	13	27.0	0.8
6.8	30	20	12.5	27.0	0.8	36	24	17	30.0	0.8
10.0	30	24	16	27.0	0.8	44	25	17	35.0	0.8

ANY SPECIAL VALUE ARE ACCEPTABLE, ITS SIZE TO BE PROVIDED UPON REQUESTED
SIZE MAYBE CHANGED W/O NOTICE. SPECIAL SIZE IS ACCEPTABLE

- 如有需特殊尺寸 / 容量-請洽本公司.
- 以上為參考尺寸,如有更動不另行通知.