


MPT

Axial lead, Round
Series

■ 1) Dimensions(外觀型式):
(臥式圓柱型)



■ 2) Specifications(產品特性):

- (a) Capacitance Tolerance (容量誤差) : ±10% (K) OR ±5% (J) at 1K HZ
- (b) MAX Dissipation Factor (最大損失角) : MAX 0.075% at 1K Hz 25°C
- (c) Temp Range (工作溫度範圍) : - 55°C ~ +105°C *
- (d) Insulation Resistance(絕緣值) : 10,000 MΩ x μF
30,000 MΩ Min.
- (e) Life Test (壽命測試) : 1000 Hours at 85°C at 150% Rated Voltage
(印加150%的工作電壓於85°C/1000小時)

■ 3) MAX SIZE(本體最大尺寸表 L x D)

Unit : mm

W.V. CAP. (μF)	SIZE	100 VDC			250 VDC		
		D max.	L max.	∅ d	D max.	L max.	∅ d
1.0		9.5	25	0.8	10.5	31	0.8
2.2		11.5	31	0.8	15	31	0.8
3.3		13	31	0.8	17	31	0.8
4.0		15	31	0.8	19	31	0.8
4.7		16	31	0.8	20	31	1.0
5.6		17.5	31	0.8	21.5	31	1.0
6.8		19.5	31	0.8	23	31	1.0
8.2		17	46	0.8	21	46	1.0
10.0		18.5	46	0.8	23	46	1.0
15.0		22.5	46	1.0	24.5	56	1.0
22.0		24	56	1.0	28.5	61	1.0
30		28.5	56	1.0	32	61	1.0
33.0		29.5	56	1.0	34	61	1.0
47.0		35.5	56	1.0	40.5	61	1.0
68.0		41	56	1.0			
82.0		41.5	61	1.0			

ANY SPECIAL VALUE ARE ACCEPTABLE, ITS SIZE TO BE PROVIDED UPON REQUESTED
SIZE MAYBE CHANGED W/O NOTICE. SPECIAL SIZE IS ACCEPTABLE

- 如有需特殊尺寸 / 容量-請洽本公司.
- 以上為參考尺寸,如有更動不另行通知