

三相電容器靜態開關

Three Phase Thyristor Switch

型號規格選擇 Choice of Specification & Models

〈3相2線零點觸發控制 (3Φ2W)〉



(圖一)



(圖二)




(圖三)



(圖四)



(圖五)



(圖六)

補助電壓 assistance voltage	主電源電壓 main power voltage	額定電流 rated current	型號 model (3Φ2W)	長 L (mm)	寬 W (mm)	高 H (mm)	圖 P
220V	208V~240V	35A	JK2PSZT-22035	220	142	154	1
		50A	JK2PSZT-22050	243	142	154	2
		60A	JK2PSZT-22060	243	142	154	2
		80A	JK2PSZT-22080	243	142	154	2
		100A	JK2PSZT-22100	243	142	154	2
		125A	JK2PSZT-22125	305	141	172	3
		160A	JK2PSZT-22160	305	141	172	3
		180A	JK2PSZT-22180	355	141	172	4
		225A	JK2PSZT-22225	400	263	210	5
		250A	JK2PSZT-22250	400	263	210	5
		300A	JK2PSZT-22300	400	263	210	5
		350A	JK2PSZT-22350	527	306	246	6
		400A	JK2PSZT-22400	527	306	246	6
		220V	380V~480V	35A	JK2PSZT-48035	220	142
50A	JK2PSZT-48050			243	142	154	2
60A	JK2PSZT-48060			243	142	154	2
80A	JK2PSZT-48080			243	142	154	2
100A	JK2PSZT-48100			243	142	154	2
125A	JK2PSZT-48125			305	141	172	3
160A	JK2PSZT-48160			305	141	172	3
180A	JK2PSZT-48180			355	141	172	4
225A	JK2PSZT-48225			400	263	210	5
250A	JK2PSZT-48250			400	263	210	5
300A	JK2PSZT-48300			400	263	210	5
350A	JK2PSZT-48350			527	306	246	6
400A	JK2PSZT-48400			527	306	246	6
220V	500V~600V			35A	JK2PSZT-60035	220	142
		50A	JK2PSZT-60050	243	142	154	2
		60A	JK2PSZT-60060	243	142	154	2
		80A	JK2PSZT-60080	243	142	154	2
		100A	JK2PSZT-60100	243	142	154	2
		125A	JK2PSZT-60125	305	141	172	3
		160A	JK2PSZT-60160	305	141	172	3
		180A	JK2PSZT-60180	355	141	172	4
		225A	JK2PSZT-60225	400	263	210	5
		250A	JK2PSZT-60250	400	263	210	5
		300A	JK2PSZT-60300	400	263	210	5
		350A	JK2PSZT-60350	527	306	246	6
		400A	JK2PSZT-60400	527	306	246	6



三相電容器靜態開關

Three Phase Thyristor Switch



功率因素盤專用 for power factor disc use only

- IEC60158-2
- EN61000-6-4
- EN61000-6-2



Quality

服務

Service 誠信

互利

Honest

品質

Mutual Benefit