

# 2701 Ethernet Multimeter/Data Acquisition System

## DC CHARACTERISTICS<sup>1</sup>

CONDITIONS: MED (1 PLC)<sup>2</sup> or 10 PLC or MED (1 PLC) with Digital Filter of 10

FUNCTION	RANGE	RESOLUTION	TEST CURRENT ±5% OR BURDEN VOLTAGE	INPUT RESISTANCE OR OPEN CKT. VOLTAGE <sup>3</sup>	ACCURACY: ±(ppm of reading + ppm of range) (ppm = parts per million) e.g., 10ppm = 0.001%			TEMPERATURE COEFFICIENT 0°-18°C & 28°-50°C
					24 Hour <sup>4</sup> 23°C±1°	90 Day 23°C±5°	1 Year 23°C±5°	
Voltage <sup>11</sup>	100.0000 mV	0.1 µV		>10 GΩ	15 + 30	25 + 35	30 + 35	(1 + 5)/°C
	1.000000 V	1.0 µV		>10 GΩ	15 + 6	25 + 7	30 + 7	(1 + 1)/°C
	10.0000 V	10 µV		>10 GΩ	10 + 4	20 + 5	30 + 5	(1 + 1)/°C
	100.0000 V	100 µV		10 MΩ ± 1%	15 + 6	35 + 9	45 + 9	(5 + 1)/°C
	1000.000 V <sup>5</sup>	1 mV		10 MΩ ± 1%	20 + 6	35 + 9	50 + 9	(5 + 1)/°C
Resistance <sup>6,8</sup>	100.0000 Ω	100 µΩ	1 mA	6.9 V	20 + 20	80 + 20	100 + 20	(8 + 1)/°C
	1.000000 kΩ	1 mΩ	1 mA	6.9 V	20 + 6	80 + 6	100 + 6	(8 + 1)/°C
	10.000000 kΩ	10 mΩ	100 µA	6.9 V	20 + 6	80 + 6	100 + 6	(8 + 1)/°C
	100.0000 kΩ	100 mΩ	10 µA	12.8 V	20 + 6	80 + 10	100 + 10	(8 + 1)/°C
	1.000000 MΩ	1.0 Ω	10 µA	12.8 V	20 + 6	80 + 10	100 + 10	(8 + 1)/°C
	10.00000 MΩ <sup>7</sup>	10 Ω	0.7 µA // 10MΩ	7.0 V	150 + 6	200 + 10	400 + 10	(70 + 1)/°C
	100.0000 MΩ <sup>7</sup>	100 Ω	0.7 µA // 10MΩ	7.0 V	800 + 30	2000 + 30	2000 + 30	(385 + 1)/°C
Continuity (2W) <sup>21</sup>	1.000 kΩ	100 mΩ	1 mA	6.9 V	40 + 100	100 + 100	100 + 100	(8 + 1)/°C
Current	20.00000 mA	10 nA	<0.2 V		60 + 30	300 + 80	500 + 80	(50 + 5)/°C
	100.0000 mA	100 nA	<0.1 V		100 + 300	300 + 800	500 + 800	(50 + 50)/°C
	1.000000 A	1.0 µA	<0.5 V <sup>9</sup>		200 + 30	500 + 80	800 + 80	(50 + 5)/°C
	3.000000 A	10 µA	<1.5 V <sup>9</sup>		1000 + 15	1200 + 40	1200 + 40	(50 + 5)/°C

Channel (Ratio)<sup>10</sup> Ratio Accuracy = Accuracy of selected Channel Range + Accuracy of Paired Channel Range

Channel (Average)<sup>10</sup> Average Accuracy = Accuracy of selected Channel Range + Accuracy of Paired Channel Range

## TEMPERATURE<sup>19</sup>

(Display in °C, °F, or K. Exclusive of probe errors.)

Thermocouples (Accuracy based on ITS-90.)

Type	Range	Resolution	90 Day/1 Year (23°C ±5°C)			Temperature Coefficient 0°-18°C & 28°-50°C
			Relative to Simulated Reference Junction	Using 77XX Module		
J	-200 to +760°C	0.001°C	0.2°C	1.0°C		0.03°C/°C
K	-200 to +1372°C	0.001°C	0.2°C	1.0°C		0.03°C/°C
N	-200 to +1300°C	0.001°C	0.2°C	1.0°C		0.03°C/°C
T	-200 to +400°C	0.001°C	0.2°C	1.0°C		0.03°C/°C
E	-200 to +1000°C	0.001°C	0.2°C	1.0°C		0.03°C/°C
R	0 to +1768°C	0.1°C	0.6°C	1.8°C		0.03°C/°C
S	0 to +1768°C	0.1°C	0.6°C	1.8°C		0.03°C/°C
B	+350 to +1820°C	0.1°C	0.6°C	1.8°C		0.03°C/°C

### 4-Wire RTD:

(100Ω platinum [PT100], D100, F100, PT385, PT3916, or user type, Offset compensation On)

-200° to 630°C	0.01°C	0.06°C	0.003°C/°C
----------------	--------	--------	------------

Thermistor: (2.2kΩ, 5kΩ, and 10kΩ)<sup>20</sup>

-80° to 150°C	0.01°C	0.08°C	0.002°C/°C
---------------	--------	--------	------------

## DC SYSTEM SPEEDS<sup>15,18</sup>

RANGE CHANGES<sup>16</sup>: 50/s (42/s) (excludes 4 Wire Ohms).

FUNCTION CHANGES<sup>16</sup>: 50/s (42/s).

AUTORANGE TIME<sup>16</sup>: <30ms.

ASCII READINGS TO RS-232 (115.2k BAUD): 300/s.

MAX. INTERNAL TRIGGER RATE: 2800/s.

MAX. EXTERNAL TRIGGER RATE: 2000/s.

## DC MEASUREMENT SPEEDS<sup>15</sup>

Single Channel, 60Hz (50Hz) Operation

FUNCTION	DIGITS	READINGS/s	PLCs
DCV, DCI, Ω (<10M), Thermocouple, Thermistor	6.5 <sup>12,16</sup>	5 (4)	10
	6.5 <sup>16</sup>	35 (24)	1
	6.5 <sup>12,16</sup>	50 (48)	1
	5.5 <sup>12,16</sup>	150 (120)	0.1
	5.5 <sup>16,17</sup>	300 (240)	0.1
	5.5 <sup>17</sup>	500 (400)	0.1
4WΩ (<10M)	4.5 <sup>17</sup>	3000 (3000)	0.006
	3.5 <sup>17</sup>	3500 (3500)	0.002
	6.5 <sup>16</sup>	1.4 (1.1)	10
4WΩ 0Comp, RTD	6.5 <sup>16</sup>	15 (12)	1
	5.5 <sup>16,17</sup>	33 (25)	0.1
	6.5 <sup>16,17</sup>	0.9 (0.7)	10
Channel (Ratio), Channel (AVG)	6.5 <sup>16,17</sup>	8 (6.4)	1
	5.5 <sup>16,17</sup>	18 (14.4)	0.1
	6.5 <sup>16,17</sup>	2.5 (2)	10
	6.5 <sup>16,17</sup>	15 (12)	1
	5.5 <sup>16,17</sup>	25 (20)	0.1

## Multiple Channels Into Memory<sup>15,18</sup>

7710 Scanning DCV	500/s
7710 Scanning with Limits or Time Stamp On	500/s
7710 Scanning DCV alternating 2WΩ	115/s
7710 Scanning Temperature (T/C)	500/s
7700 and 7708 Scanning Temperature (T/C)	80/s

## Multiple Channels Into and Out of Memory<sup>15,16,17,18</sup>

7710 Scanning DCV	440/s
7710 Scanning with Limits or Time Stamp On	440/s
7710 Scanning DCV alternating 2WΩ	110/s
7710 Scanning Temperature (T/C)	440/s
7700 and 7708 Scanning Temperature (T/C)	80/s
7702 Scanning DCV	75/s

# 2701 Ethernet Multimeter/Data Acquisition System

## DC SPEED vs. NOISE REJECTION

Rate	Filter	Readings/s <sup>12</sup>	Digits	RMS Noise		
				10V Range	NMRR	CMRR <sup>14</sup>
10	50	0.1 (0.08)	6.5	<2.5 $\mu$ V	110 dB <sup>13</sup>	140 dB
1	Off	15 (12)	6.5	<6 $\mu$ V	90 dB <sup>13</sup>	140 dB
0.1	Off	500 (400)	5.5	<40 $\mu$ V	-	80 dB
0.006	Off	3000 (3000)	4.5	<300 $\mu$ V	-	80 dB
0.002	Off	3500 (3500)	3.5	<1 mV	-	60 dB

## DC MEASUREMENT CHARACTERISTICS

### DC Volts

A-D LINEARITY: 2.0 ppm of reading + 1.0 ppm of range.

### INPUT IMPEDANCE:

**100mV-10V Ranges:** Selectable >10G $\Omega$ // with <400pF or 10M $\Omega$   $\pm$ 1%.  
**100V, 1000V Ranges:** 10M $\Omega$   $\pm$ 1%.

**EARTH ISOLATION:** 500V peak, >10G $\Omega$  and <300pF any terminal to chassis.

**INPUT BIAS CURRENT:** <75pA at 23°C.

**COMMON MODE CURRENT:** <500nApp at 50Hz or 60Hz.

**AUTOZERO ERROR:** Add  $\pm$ (2ppm of range error +5 $\mu$ V) for <10 minutes and  $\pm$ 1°C.

**INPUT PROTECTION:** 1000V, all ranges, 300V with plug-in modules.

### Resistance

**MAX 4W $\Omega$  LEAD RESISTANCE:** 10% of range per lead for 100 $\Omega$  and 1k $\Omega$  ranges; 1k $\Omega$  per lead for all other ranges.

**OFFSET COMPENSATION:** Selectable on 4W $\Omega$  100 $\Omega$ , 1k $\Omega$ , and 10k $\Omega$  ranges.

**CONTINUITY THRESHOLD:** Adjustable 1 to 1000 $\Omega$ .

**INPUT PROTECTION:** 1000V, all Source Inputs, 350V Sense Inputs, 300V with plug-in modules.

### DC Current

**SHUNT RESISTORS:** 100mA-3A, 0.1 $\Omega$ . 20mA, 5 $\Omega$ .

**INPUT PROTECTION:** 3A, 250V fuse.

### Thermocouples

**CONVERSION:** ITS-90.

**REFERENCE JUNCTION:** Internal, External, or Simulated (Fixed).

**OPEN CIRCUIT CHECK:** Selectable per channel. Open >11.4k  $\pm$ 200 $\Omega$ .

## DC Notes

- 20% overrange except on 1000V and 3A.
- Add the following to "ppm of range" uncertainty: 100mV 15ppm, 1V and 100V 2ppm, 100 $\Omega$  30ppm, 1k $\rightarrow$ <1M $\Omega$  2ppm, 10mA and 1A 10ppm, 100mA 40ppm.
- $\pm$ 2% (measured with 10M $\Omega$  input resistance DMM, >10G $\Omega$  DMM on 10M $\Omega$  and 100M $\Omega$  ranges).
- Relative to calibration accuracy.
- For signal levels >500V, add 0.02ppm/V uncertainty for portion exceeding 500V.
- Specifications are for 4-wire  $\Omega$ , 100 $\Omega$  with offset compensation on, 77xx plug-in module with LSYNC and offset compensation on. With offset compensation on OPEN CKT. VOLTAGE is 12.8V. For 2-wire  $\Omega$  add 1.0 $\Omega$  to "ppm of range" uncertainty.
- Must have 10% matching of lead resistance in Input HI and LO.
- Add the following to "ppm of reading" uncertainty when using plug in modules:

	10 k $\Omega$	100 k $\Omega$	1 M $\Omega$	10 M $\Omega$	100 M $\Omega$
<b>All Modules:</b>				220 ppm	2200 ppm
<b>7701, 7703, 7707, and 7709 Modules:</b>	10 ppm	100 ppm	1000 ppm	1%	10%
<b>7706, 7708 Modules:</b>	5 ppm	50 ppm	500 ppm	5000 ppm	5%
<b>7710 Model 23°C <math>\pm</math>5°C:</b>	11 ppm	110 ppm	1100 ppm	1.1%	11%
<b>7710 Model Temp Coeff. &gt;28°C<math>\rightarrow</math>50°C</b>	0.3 ppm/ $^{\circ}$ C	3 ppm/ $^{\circ}$ C	30 ppm/ $^{\circ}$ C	0.03%/ $^{\circ}$ C	0.3%/ $^{\circ}$ C

- Add 1.0V when used with plug-in modules.
- For RATIO, DCV only. For AVERAGE, DCV and Thermocouples only. Available with plug-in modules only.
- Add 6 $\mu$ V to "of range" uncertainty when using Models 7701, 7703, and 7707, 3 $\mu$ V for Models 7706, 7709, and 7710.
- Auto zero off.
- For LSYNC On, line frequency  $\pm$ 0.1%. For LSYNC Off, use 60dB for  $\geq$  1PLC.
- For 1k $\Omega$  unbalance in LO lead.
- Speeds are for 60Hz (50Hz) operation using factory defaults operating conditions (\*RST). Autorange off, Display off, Limits off, Trigger delay = 0.
- Speeds include measurements and data transfer out the ethernet (reading elements only). (100BaseT Ethernet, 3 meter RJ-45 crossover cable, PIII-800, Windows version 98 SE, VB version 6.0, direct Winsocket interface).
- Sample count = 1000 (into memory buffer), auto zero off.
- Auto zero off, NPLC = 0.002.
- Additional Uncertainty

Type	Range	7710 Module Using CJC
J	0 to +760°C	1.5°C
K	0 to +1372°C	—
N	0 to +1300°C	0.5°C
T	0 to +400°C	0.5°C
E	0 to +1000°C	0.5°C
R	+400 to +1768°C	0.9°C
S	+400 to +1768°C	0.9°C
B	+1100 to +1820°C	0.9°C

Type	Range	Plug-In Modules					
		Front Terminals Sim. Ref. Junction	7709 Sim. Ref. Junction	7701, 7703, 7707 Sim. Ref. Junction	7700 and 7708 Using CJC	7706 Using CJC	7710 Using CJC
J	-200 to 0°C	0.1	0.1	0.3	0.8	1.6	4.5
K	-200 to 0°C	0.2	0.2	0.4	0.8	1.6	1
N	-200 to 0°C	0.3	0.3	0.6	0.8	1.6	2.5
T	-200 to 0°C	0.2	0.1	0.4	0.8	1.6	2.5
E	-200 to 0°C	-	0.1	0.3	0.8	1.6	2.5
R	0 to +400°C	0.4	0.6	1.2	0.5	1.0	2.2
S	0 to +400°C	0.4	0.6	1.2	0.5	1.0	2.2
B	+350 to +1100°C	0.8	0.3	1.7	0.5	1.0	2.2

- For lead resistance >0 $\Omega$ , add the following uncertainty/ $\Omega$  for measurement temperatures of:

		70 $^{\circ}$ -100 $^{\circ}$ C	100 $^{\circ}$ -150 $^{\circ}$ C
<b>2.2 k<math>\Omega</math></b>	(44004)	0.22°C	1.11°C
<b>5.0 k<math>\Omega</math></b>	(44007)	0.10°C	0.46°C
<b>10 k<math>\Omega</math></b>	(44006)	0.04°C	0.19°C

- Front Panel resolution is limited to 0.1 $\Omega$ .

# 2701 Ethernet Multimeter/Data Acquisition System

## AC SPECIFICATIONS<sup>1</sup>

Function	Range	Resolution	Calibration Cycle	Accuracy: ±(% of reading + % of range), 23°C ±5°C				
				3 Hz-10 Hz <sup>14</sup>	10 Hz-20 kHz <sup>8</sup>	20 kHz-50 kHz	50 kHz-100 kHz	100 kHz-300 kHz
Voltage <sup>2</sup>	100.0000 mV	0.1 μV	90 Days (all ranges)	0.35 + 0.03	0.05 + 0.03	0.11 + 0.05	0.6 + 0.08	4.0 + 0.5
	1.000000 V	1.0 μV		1 Year (all ranges)	0.35 + 0.03	0.06 + 0.03	0.12 + 0.05	0.6 + 0.08
	10.00000 V	10 μV	(Temp. Coeff.) <sup>9</sup> C <sup>3</sup>		0.035 + 0.003	0.005 + 0.003	0.006 + 0.005	0.01 + 0.006
	100.0000 V	100 μV	3 Hz-10 Hz	10 Hz-3 kHz	3 kHz-5kHz			
750.000 V	1.0 mV							
Current <sup>2</sup>	1.000000 A	1.0 μA	90 Day/1 Yr.	0.30 + 0.04	0.10 + 0.04	0.14 + 0.04		
	3.00000 <sup>15</sup> A	10 μA		0.35 + 0.06	0.15 + 0.06	0.18 + 0.06		
			(Temp. Coeff.) <sup>9</sup> C <sup>3</sup>	0.035 + 0.006	0.015 + 0.006	0.015 + 0.006		
Frequency <sup>4</sup> and Period	100 mV	0.333 ppm	90 Day/1 Yr.	Accuracy ±(ppm of reading + offset ppm) (3 Hz-500 kHz) (333 ms-2 μs)				
	to 750 V	3.33 ppm		80 ppm + 0.333 ppm (SLOW, 1s gate)				
		33.3 ppm		80 ppm + 3.33 ppm (MED, 100ms gate)				
				80 ppm + 33.3 ppm (FAST, 10ms gate)				

### Additional Uncertainty ±(% of reading)

Low Frequency Uncertainty	MED	FAST
20Hz - 30Hz	0.3	—
30Hz - 50Hz	0	—
50Hz - 100Hz	0	1.0
100Hz - 200Hz	0	0.18
200Hz - 300Hz	0	0.10
> 300Hz	0	0

CREST FACTOR <sup>5</sup> :	1-2	2-3	3-4	4-5
Additional Uncertainty:	0.05	0.15	0.30	0.40
Maximum Crest Factor:	5 at full-scale.			

## AC MEASUREMENT CHARACTERISTICS

### AC Volts

MEASUREMENT METHOD: AC-coupled, True RMS.  
 INPUT IMPEDANCE: 1MΩ ±2% // by <100pF.  
 INPUT PROTECTION: 1000Vp or 400VDC, 300Vrms with plug-in modules.

### AC Current

MEASUREMENT METHOD: AC-coupled, True RMS.  
 SHUNT RESISTANCE: 0.1Ω.  
 BURDEN VOLTAGE: 1A <0.5Vrms, 3A <1.5Vrms. Add 1.5Vrms when used with plug-in modules.  
 INPUT PROTECTION: 3A, 250V fuse.

### Frequency and Period

MEASUREMENT METHOD: Reciprocal Counting technique.  
 GATE TIME: SLOW 1s, MED 100ms, and FAST 10ms.

### AC General

AC CMRR<sup>6</sup>: 70dB.  
 VOLT HERTZ PRODUCT<sup>16</sup>: ≤8 × 10<sup>7</sup> Volt-Hz.

## AC MEASUREMENT SPEEDS<sup>7,13</sup>

### Single Channel, 60Hz (50Hz) Operation

Function	Digits	Readings/s	Rate	Bandwidth
ACV, ACI	6.5	2s/Reading	SLOW	3 Hz-300 kHz
	6.5	4.8 (4)	MED	30 Hz-300 kHz
	6.5 <sup>9</sup>	40 (32)	FAST	300 Hz-300 kHz
Frequency, Period	6.5	1 (1)	SLOW	3 Hz-300 kHz
	5.5	9 (9)	MED	30 Hz-300 kHz
	4.5	35 (35)	FAST	300 Hz-300 kHz
	4.5 <sup>10</sup>	65 (65)	FAST	300 Hz-300 kHz

### Multiple Channel Into Memory<sup>10,11</sup>

7710 SCANNING ACV: 440/s.  
 7710 Scanning ACV with Auto Delay On: 2s/reading.

### AC SYSTEM SPEEDS<sup>7,9,11</sup>

RANGE CHANGES<sup>12</sup>: 4/s (3/s).  
 FUNCTION CHANGES<sup>12</sup>: 4/s (3/s).  
 AUTORANGE TIME: < 3s.  
 ASCII READINGS TO RS-232 (115.2k baud): 300/s.  
 MAX. INTERNAL TRIGGER RATE: 2800/s.  
 MAX. EXTERNAL TRIGGER RATE: 2000/s.

### AC Notes

- 20% overrange except on 750V and 3A.
- Specifications are for SLOW mode and sine wave inputs >5% of range. SLOW and MED are multi-sample A/D conversions. FAST is DETector: BANDwidth 300 with nPLC = 1.0.
- Applies to 0°-18°C and 28°-50°C.
- Specifications are for square wave inputs only. Input signal must be >10% of ACV range. If input is <20mV on the 100mV range then the frequency must be >10Hz. For sinewave inputs, frequency must be >100Hz.
- Applies to non-sine waves >5Hz and <500Hz. Crest factor greater than 4.3 is guaranteed by design only.
- For 1kΩ unbalance in LO lead.
- Speeds are for 60Hz (50Hz) operation using factory defaults operating conditions (\*RST). Autorange off, Display off, Limits off, Trigger delay=0.
- For ACV inputs at frequencies of 50 or 60Hz (±10%) add the following to "% of Range" uncertainty: 100mv 0.25%, 1V 0.05%, 10V 0.13%, 100V 0.03%, 750V 0.01%.
- Auto Zero off.
- Sample count = 1000 (into memory buffer).
- DETector: BANDwidth 300 with nPLC = 0.006.
- Maximum useful limit with trigger delay = 175ms.
- Includes measurement and data transfer out Ethernet (Reading Element only). (100bTx Ethernet, 3 meter RJ-45 crossover cable, PIII-800, Windows version 98 SE, VB version 6.0, direct WinSocket interface).
- Typical uncertainties. Typical represents two sigma or 95% of manufactured units measure < 0.35% of reading and three sigma or 99.7% < 1.06% of reading.
- For signal levels >2.2A, add additional 0.4% to "of reading" uncertainty.
- 750Vac range limited to 707Vrms and 85kHz (sinewave input) or 8 × 10<sup>7</sup> Volt-Hz.

# 2701 Ethernet Multimeter/Data Acquisition System

## GENERAL SPECIFICATIONS

**EXPANSION SLOTS:** 2.  
**POWER SUPPLY:** 100V / 120V / 220V / 240V.  
**LINE FREQUENCY:** 50Hz to 60Hz and 400Hz, automatically sensed at power-up.  
**POWER CONSUMPTION:** 80VA.  
**OPERATING ENVIRONMENT:** Specified for 0°C to 50°C. Specified to 80% RH at 35°C. Altitude up to 2000 meters.  
**STORAGE ENVIRONMENT:** -40°C to 70°C.  
**BATTERY:** Lithium Ion battery-backed memory, 30 days of buffer storage @ 23°C and >4 hours charge time. Battery lifetime: 3 years @ 23°C, 1.5 years @ 50°C.  
**WARRANTY:** 3 years, excludes battery.  
**EMC:** Conforms to European Union Directive 89/336/EEC EN61326-1.  
**SAFETY:** Conforms to European Union Directive 73/23/EEC EN61010-1, CAT I.  
**VIBRATION:** MIL-PRF-28800F Class 3, Random.  
**WARM-UP:** 2 hours to rated accuracy.  
**DIMENSIONS:**  
**Rack Mounting:** 89mm high × 213mm wide × 370mm deep (3.5 in. × 8.375 in. × 14.563 in.).  
**Bench Configuration (with handle and feet):** 104mm high × 238mm wide × 370mm deep (4.125 in. × 9.375 in. × 14.563 in.).  
**SHIPPING WEIGHT:** 4.75kg (10 lbs).  
**DIGITAL I/O:** 2 inputs, 1 for triggering and 1 for hardware interlock. 5 outputs, 4 for Reading Limits and 1 for Master Limit. Outputs are TTL compatible or can sink 250mA, diode clamped to 40V.  
**TRIGGERING AND MEMORY:**  
**Window Filter Sensitivity:** 0.01%, 0.1%, 1%, 10%, or Full-scale of range (none).  
**Reading Hold Sensitivity:** 0.01%, 0.1%, 1%, or 10% of reading.  
**Trigger Delay:** 0 to 99 hrs (1ms step size).  
**External Trigger Delay:** <1ms.  
**Memory Size:** 450,000 readings.  
**MATH FUNCTIONS:** Rel, Min/Max/Average/Std Dev/Peak-to-Peak (of stored reading), Limit Test, %, 1/x, and mX + b with user defined units displayed.  
**REMOTE INTERFACE:**  
Ethernet: RJ-45 connector, TCP/IP (Auto sensed 10bT or 100bTx) and RS-232C.  
SCPI (Standard Commands for Programmable Instruments)  
**ACCESSORIES SUPPLIED:** Model 1751 Safety Test Leads, Product Information CD-ROM, Model 2701 Networking Manual, Model 2701 Getting Started Foldout, 3m crossover Ethernet cable. Software CD-ROM with IVI/VISA drivers for VB, VC/C++, LabVIEW, TestPoint, and LabWindows/CVI, and free runtime startup software.  
**ACCESSORIES AVAILABLE:**  
77XX Modules  
Extended Warranty  
ExcelLINX-1A (Excel add-in datalogger software)  
TestPoint™ Software Development Package  
**IP CONFIGURATION:** Static or DHCP  
**PASSWORD PROTECTION:** 11 characters  
**SOFTWARE:** Windows 98, NT, 2000, ME and XP compatible, Internet Explorer 5.0 or higher required. Web pages served by 2701.



1.888.KEITHLEY (U.S. only)

[www.keithley.com](http://www.keithley.com)

**KEITHLEY** 美国吉时利华南营销平台

深圳市金博宇科技有限公司

电话：0755-23107120

传真：0755-23107130 手机：13925278646

网址：<http://www.jboyu.com/>

地址：深圳市宝安区民治街道梅陇路梅陇公馆B908室

A GREATER MEASURE OF CONFIDENCE