



Features:

Horizontal installation, multi-out-puts applied in denseness installation.

For driver transformer, main transformer and smoothing choke.

Reference	Type	Number of terminal pin	DIMENSION(mm)							Maximum Output(VA)
			MAX	MAX	MAX	±0.3	±0.4	±0.5	±0.1	
			A	B	C	D	E	F	G	
CPQ2020-A	Vertical	14(8+8)	24	24	22	3.8(2.5)	5.1	20.3	0.6	92
CPQ2620-A	Vertical	12	28	32	22	3.8	7.6	25.4	0.8	170
CPQ2620-B	Vertical	12	28	32	21	3.8	7.6	25.4	0.6	170
CPQ2625-A	Vertical	12	28.5	31	28	3.8	7.5	25.5	0.7	195
CPQ3220-A	Vertical	12	33	35	24	5	7.5	30	0.8	232
CPQ3220-B	Vertical	12	33	36	22	5.1	7.6	30.5	0.8	232
CPQ3225-A	Vertical	12	35.5	35	27	5	7.4	30	0.8	280
CPQ3230-A	Vertical	12	33	38	32	5.05	7.8	30.3	0.8	331
CPQ3535-A	Vertical	12	37	41	38.5	5	10	35	0.8	452
CPQ4040-A	Vertical	12	41	44	43	5	15.1	38	0.8	598
CPQ5050-A	Vertical	12	52	53	54	7.62	15.24	45.72	1.2	1045

Note: The output power is only for forward model and the frequency at 100KHz.