

GENERAL TOLERANCE

X <sub>1</sub> ± 5.0°	X <sub>2</sub> ± 0.30
X <sub>1</sub> ± 3.0°	X <sub>1</sub> ± 0.25
.XX ± 2.0°	.XX ± 0.15
.XXX ± 1.0°	.XXX ± 0.10


HIGH	SOCKET(H)	PLUG(H)
3.0	2.2	0.8
3.5	2.2	1.3
4.0	3.0	1.5
4.5	3.5	1.0
5.0	3.0	2.0
5.5	3.5	2.0
6.0	4.0	2.0
6.5	4.5	2.0

	A	B	C	D	E
8P	4.70	1.50	2.40	3.40	2.00
10P	5.20	2.00	2.90	3.90	2.50
12P	5.70	2.50	3.40	4.40	3.00
14P	6.20	3.00	3.90	4.90	3.50
16P	6.70	3.50	4.40	5.40	4.00
18P	7.20	4.00	4.90	5.90	4.50
20P	7.70	4.50	5.40	6.40	5.00
22P	8.20	5.00	5.90	6.90	5.50
24P	8.70	5.50	6.40	7.40	6.00
26P	9.20	6.00	6.90	7.90	6.50
28P	9.70	6.50	7.40	8.40	7.00
30P	10.2	7.00	7.90	8.90	7.50
32P	10.7	7.50	8.40	9.40	8.00
34P	11.2	8.00	8.90	9.90	8.50
36P	11.7	8.50	9.40	10.40	9.00
38P	12.2	9.00	9.90	10.90	9.50
40P	12.7	9.50	10.40	11.40	10.0
42P	13.2	10.0	10.90	11.90	10.5
44P	13.7	10.5	11.40	12.40	11.0
46P	14.2	11.0	11.90	12.90	11.5
48P	14.7	11.5	12.40	13.40	12.0
50P	15.2	12.0	12.90	13.90	12.5
60P	17.7	14.5	15.50	16.40	15.0
80P	22.7	19.5	20.50	21.40	20.0
100P	27.7	24.5	25.50	26.40	25.0

MICRO BOARD-TO-BOARD PITCH0.5mm (母)

深圳市威鑫联电子有限公司

Customer:	Approval:	Unit	Scale	Date
Drawing No:	Check:	mm	5:1	02.07.26



Pin Longger:

P/NO:

Signatuer: