



PIN#	SYMBOL
B1	SD1
B2	FLM
B3	ME
B4	LOAD
B5	CP
B6	SD2
B7	VDD(5.0V)
B8	VSS
B9	VLCD
B10	VADV

PIN#	SYMBOL
A1	VSS
A2	VDD(5.0V)
A3	VADV
A4	RS
A5	R/W
A6	E
A7-A14	DB0-DB7
A15	/CS
A16	/RES
A17	VLCD
A18	NC
A19	NC
A20	NC

NOTES:

1. ALL DIMENSIONS ARE mm.
2. VIEWING DIRECTION: 6 O'CLOCK.
3. DRIVE METHOD: 1/64 DUTY; 1/9 BIAS.
4. LCD OPERATING VOLTAGE: 17.3 V.
5. OPERATING TEMP. -20°C TO +70°C.
6. STORAGE TEMP. -30°C TO +80°C.
7. DRIVER IC: 6X SCND080G\_A(SEGMENTS), 2XSCND064G(COMMONS)
8. REFER TO MODULE PRODUCT SPECIFICATIONS FOR SPECIFIC CONFIGURATIONS AND BILL OF MATERIALS.
9. 产品及包装需符合RoHS。

DETAIL FOR DOTS  
SCALE:10:1

