



NATL SEMICOND (LINEAR)

T-73-53

LM193/LM293/LM393, LM2903

LM193/LM293/LM393, LM2903 Low Power Low Offset Voltage Dual Comparators

General Description


The LM193 series consists of two independent precision voltage comparators with an offset voltage specification as low as 2.0 mV max for two comparators which were designed specifically to operate from a single power supply over a wide range of voltages. Operation from split power supplies is also possible and the low power supply current drain is independent of the magnitude of the power supply voltage. These comparators also have a unique characteristic in that the input common-mode voltage range includes ground, even though operated from a single power supply voltage.

Application areas include limit comparators, simple analog to digital converters; pulse, squarewave and time delay generators; wide range VCO; MOS clock timers; multivibrators and high voltage digital logic gates. The LM193 series was designed to directly interface with TTL and CMOS. When operated from both plus and minus power supplies, the LM193 series will directly interface with MOS logic where their low power drain is a distinct advantage over standard comparators.


Advantages

- High precision comparators
- Reduced V_{OS} drift over temperature


Schematic and Connection Diagrams



Metal Can Package



Order Number LM193H,
LH193H/883*,
LM193AH, LM193AH/883,
LM293H, LM293AH, LM393H
or LM393AH
See NS Package Number H08C



Order Number LM193J/883*,
LM193AJ/883,
LM393J, LM393AJ,
LM393M, LM2903M, LM393N,
LM2903J or LM2903N
See NS Package Number J08A,
M08A or N08E

TL/H/5708-1

*Also available per JM38510/11202

Absolute Maximum Ratings

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

(Note 10)

Supply Voltage, V₊

Differential Input Voltage (Note 8)

Input Voltage

Input Current ($V_N < -0.3$ VDC) (Note 3)

Power Dissipation (Note 1)

Molded DIP

Metal Can

Small Outline Package

Output Short-Circuit to Ground (Note 2)

Operating Temperature Range

LM193/LM393A

LM293/LM2903

LM193/LM393A

LM2903

Storage Temperature Range

Lead Temperature (Soldering, 10 seconds)

Soldering Information

Dual-In-Line Package

Soldering (10 seconds)

Small Outline Package

Vapor Phase (60 seconds)

Infrared (15 seconds)

See AN-450 "Surface Mounting Methods and Their Effect on Product Reliability" for other methods of soldering surface mount devices.

ESD rating (1.5 kΩ in series with 100 pF)

Electrical Characteristics ($V^+ = 5$ VDC, $T_A = 25^\circ\text{C}$, unless otherwise stated)

| Parameter | Conditions | LM193A | | | LM293A, LM393A | | | LM193 | | | LM293, LM393 | | | LM2903 | | | |
|----------------------------------|--|--------|-------------|------|----------------|------|-------------|-------|-------------|------|--------------|------|-------------|--------|-------------|------|--------------------------|
| | | Min | Typ | Max | Min | Typ | Max | Min | Typ | Max | Min | Typ | Max | Min | Typ | Max | Units |
| Input Offset Voltage (Note 9) | | ±1.0 | ±2.0 | ±1.0 | ±2.0 | ±1.0 | ±2.0 | ±1.0 | ±2.0 | ±1.0 | ±1.0 | ±1.0 | ±2.0 | ±1.0 | ±2.0 | ±7.0 | mVDC |
| Input Bias Current | $I_{IN}(+)$ or $ I_{IN}(-) $ with Output in Linear Range, $V_{CM} = 0$ V (Note 5) | 25 | 100 | 25 | 250 | 25 | 250 | 25 | 250 | 25 | 250 | 25 | 250 | 25 | 250 | 250 | nADC |
| Input Offset Current | $ I_{IN}(+) - I_{IN}(-) V_{CM} = 0$ V | ±3.0 | ±25 | ±3.0 | ±50 | ±3.0 | ±50 | ±3.0 | ±25 | ±3.0 | ±50 | ±50 | ±5.0 | ±5.0 | ±5.0 | ±50 | nADC |
| Input Common Mode Voltage Range | $V^+ = 30$ VDC (Note 6) | 0 | $V^+ - 1.5$ | 0 | $V^+ - 1.5$ | 0 | $V^+ - 1.5$ | 0 | $V^+ - 1.5$ | 0 | $V^+ - 1.5$ | 0 | $V^+ - 1.5$ | 0 | $V^+ - 1.5$ | 0 | V ⁺ - 1.5 VDC |
| Supply Current | $R_L = \infty$ on All Comparators, $R_L = \infty$ on All Amps, $V^+ = 36$ VDC | 0.4 | 1 | 0.4 | 1 | 0.4 | 1 | 0.4 | 1 | 0.4 | 1 | 0.4 | 1 | 0.4 | 1 | 1.0 | mADC |
| Voltage Gain | $R_L \geq 15$ kΩ, $V^+ = 15$ VDC $V_O = 1$ VDC to 11 VDC | 50 | 200 | 50 | 200 | 50 | 200 | 50 | 200 | 50 | 200 | 50 | 200 | 25 | 100 | 25 | mADC |
| Large Signal Response Time | $V_{IN} = \text{TTL Logic Swing}, V_{REF} = 1.4$ VDC $V_{RL} = 5$ VDC, $R_L = 5.1$ kΩ | 300 | | 300 | | 300 | | 300 | | 300 | | 300 | | 300 | | 300 | ns |
| Response Time | $V_{RL} = 5$ VDC, $R_L = 5.1$ kΩ (Note 7) | 1.3 | | 1.3 | | 1.3 | | 1.3 | | 1.3 | | 1.3 | | 1.3 | | 1.5 | μs |
| Output Sink Current | $V_{IN}(-) = 1$ VDC, $V_{IN}(+) = 0$, $V_O \leq 1.5$ VDC | 6.0 | 16 | 6.0 | 16 | 6.0 | 16 | 6.0 | 16 | 6.0 | 16 | 6.0 | 16 | 6.0 | 16 | 6.0 | mADC |
| Saturation Voltage | $V_{IN}(-) = 1$ VDC, $V_{IN}(+) = 0$, $I_{SINK} \leq 4$ mA | 250 | 400 | 250 | 400 | 250 | 400 | 250 | 400 | 250 | 400 | 250 | 400 | 250 | 400 | 400 | mVDC |
| Output Leakage Current | $V_{IN}(-) = 0$, $V_{IN}(+) = 1$ VDC, $V_O = 5$ VDC | 0.1 | | 0.1 | | 0.1 | | 0.1 | | 0.1 | | 0.1 | | 0.1 | | 0.1 | nADC |

Electrical Characteristics ($V^+ = 5 \text{ V}_{\text{DC}}$) (Note 4)

| Parameter | Conditions | LM193A | | LM293A, LM393A | | LM193 | | LM293, LM393 | | LM2903 | | Units |
|---------------------------------|--|---------|-------------|----------------|-------------|---------|-------------|--------------|-------------|---------|-------------|---------------------------|
| | | Min Typ | Max | Min Typ | Max | Min Typ | Max | Min Typ | Max | Min Typ | Max | |
| Input Offset Voltage | (Note 9) | | ± 4.0 | | ± 4.0 | | ± 9 | | ± 9 | | ± 15 | mV _{DC} |
| Input Offset Current | $ I_{IN(+)} - I_{IN(-)} , V_{CM} = 0 \text{ V}$ | | ± 100 | | ± 150 | | ± 100 | | ± 150 | | ± 50 | nA _{DC} |
| Input Bias Current | $ I_{IN(+)} + I_{IN(-)}$ with Output in Linear Range, $V_{CM} = 0 \text{ V}$ (Note 5) | | 300 | | 400 | | 300 | | 400 | | 200 | 500 nA _{DC} |
| Input Common Mode Voltage Range | $V^+ = 30 \text{ V}_{\text{DC}}$ (Note 6) | 0 | $V^+ - 2.0$ | 0 | $V^+ - 2.0$ | 0 | $V^+ - 2.0$ | 0 | $V^+ - 2.0$ | 0 | $V^+ - 2.0$ | V _{DC} |
| Saturation Voltage | $V_{IN(-)} = 1 \text{ V}_{\text{DC}}, V_{IN(+)} = 0, SINK \leq 4 \text{ mA},$ | | 700 | | 700 | | 700 | | 700 | | 400 | 700 mV _{DC} |
| Output Leakage Current | $V_{IN(-)} = 0, V_{IN(+)} = 1 \text{ V}_{\text{DC}}, V_O = 30 \text{ V}_{\text{DC}}$ | | 1.0 | | 1.0 | | 1.0 | | 1.0 | | 1.0 | μA_{DC} |
| Differential Input Voltage | Keep All V_{IN} 's $\geq 0 \text{ V}_{\text{DC}}$ (or V^- , if Used), (Note 8) | 36 | | 36 | | 36 | | 36 | | 36 | | 36 V _{DC} |

Note 1: For operating at high temperatures, the LM393/LM393A and LM2903 must be derated based on a 125°C maximum junction temperature and a thermal resistance of 170°C/W which applies for the device soldered in a printed circuit board, operating in a still air ambient. The LM193/LM193A/LM293/LM393 must be derated based on a 150°C maximum junction temperature. The low bias dissipation and the "ON-OFF" characteristic of the outputs keeps the chip discharge very small ($I_D \leq 100 \text{ nA}$), provided the output transistors are allowed to saturate.

Note 2: Short circuits from the output to V^+ can cause excessive heating and eventual destruction. When considering short circuits to ground, the maximum output current is approximately 20 mA independent of the magnitude of V^+ .

Note 3: This input current will only exist when the voltage at any of the input leads is driven negative. It is due to the collector-base junction of the input PNP transistors becoming forward biased and thereby acting as input diode clamp diodes. In addition to this diode action, there is also lateral NPN parasitic transistor action on the IC chip. This transistor action can cause the output voltages of the comparators to go to the V^+ voltage level (or to ground for a large overdrive) for the time duration that an input is driven negative. This is not destructive and normal output states will re-establish when the input voltage, which was negative, again returns to a value greater than $-0.3 \text{ V}_{\text{DC}}$.

Note 4: These specifications are limited to $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$, for the LM193/LM193A. With the LM293/LM393A all temperature specifications are limited to $-25^\circ\text{C} \leq T_A \leq +85^\circ\text{C}$ and the LM393/LM2903 temperature specifications are limited to $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$. The LM2903 is limited to $-40^\circ\text{C} \leq T_A \leq +65^\circ\text{C}$.

Note 5: The direction of the input current is out of the IC due to the PNP input stage. This current is essentially constant, independent of the state of the output so no loading change exists on the reference or input lines.

Note 6: The input common-mode voltage or either input signal voltage should not be allowed to go negative by more than 0.3V_T. The upper end of the common-mode voltage range is $V^+ - 1.5 \text{ V}$ at 25°C, but either or both inputs can go to 36 V_{DC} without damage, independent of the magnitude of V^+ .






Note 7: The response time specified is for a 100 mV input step with 5 mV overdrive. For larger overdrive signals 300 ns can be obtained, see typical performance characteristics section.

Note 8: Positive excursions of input voltage may exceed the power supply level. As long as the other voltage remains within the common-mode range, the comparator will provide a proper output state. The low input voltage state must not be less than $-0.3 \text{ V}_{\text{DC}}$ (or 0.3 V_T) below the magnitude of the negative power supply, if used.






Note 9: At output switch point, $V_O \approx 1.4 \text{ V}_{\text{DC}}, R_S = 0 \Omega$, with V^+ from 5 V_{DC} to 30 V_{DC}; and over the full input common-mode range (0 V_{DC} to $V^+ - 1.5 \text{ V}_{\text{DC}}$), at 25°C.

Note 10: Refer to RETS193AX for LM193AH military specifications and to RETS193X for LM193H military specifications.

LM193/LM293/LM393, LM2903

Typical Performance Characteristics LM193/LM293/LM393, LM193A/LM293A/LM393A**Response Time for Various Input Overdrives—Negative Transition****Response Time for Various Input Overdrives—Positive Transition**

TL/H/5709-3

Typical Performance Characteristics LM2903**Response Time for Various Input Overdrives—Negative Transition****Response Time for Various Input Overdrives—Positive Transition**

TL/H/5709-4

NATL SEMICOND (LINEAR)

LM193/LM293/LM393, LM2903

Application Hints

The LM193 series are high gain, wide bandwidth devices which, like most comparators, can easily oscillate if the output lead is inadvertently allowed to capacitively couple to the inputs via stray capacitance. This shows up only during the output voltage transition intervals as the comparator change states. Power supply bypassing is not required to solve this problem. Standard PC board layout is helpful as it reduces stray input-output coupling. Reducing the input resistors to $< 10\text{ k}\Omega$ reduces the feedback signal levels and finally, adding even a small amount (1.0 to 10 mV) of positive feedback (hysteresis) causes such a rapid transition that oscillations due to stray feedback are not possible. Simply socketing the IC and attaching resistors to the pins will cause input-output oscillations during the small transition intervals unless hysteresis is used. If the input signal is a pulse waveform, with relatively fast rise and fall times, hysteresis is not required.




All pins of any unused comparators should be grounded.

The bias network of the LM193 series establishes a drain current which is independent of the magnitude of the power supply voltage over the range of from 2.0 V_{DC} to 30 V_{DC}.

It is usually unnecessary to use a bypass capacitor across the power supply line.

The differential input voltage may be larger than V⁺ without damaging the device (see Note 8). Protection should be provided to prevent the input voltages from going negative more than -0.3 V_{DC} (at 25°C). An input clamp diode can be used as shown in the applications section.


The output of the LM193 series is the uncommitted collector of a grounded-emitter NPN output transistor. Many collectors can be tied together to provide an output OR'ing function. An output pull-up resistor can be connected to any available power supply voltage within the permitted supply voltage range and there is no restriction on this voltage due to the magnitude of the voltage which is applied to the V⁺ terminal of the LM193 package. The output can also be used as a simple SPST switch to ground (when a pull-up resistor is not used). The amount of current which the output device can sink is limited by the drive available (which is independent of V⁺) and the β of this device. When the maximum current limit is reached (approximately 16 mA), the output transistor will come out of saturation and the output voltage will rise very rapidly. The output saturation voltage is limited by the approximately 60Ω r_{SAT} of the output transistor. The low offset voltage of the output transistor (1.0 mV) allows the output to clamp essentially to ground level for small load currents.

Typical Applications (V⁺ = 5.0 V_{DC})**Basic Comparator****Driving CMOS****Driving TTL**


TL/H/5709-2

Typical Applications (Continued)

Squarewave Oscillator




Pulse Generator




*For large ratios of R_1/R_2 ,
 D_1 can be omitted.

Crystal Controlled Oscillator



Two-Decade High-Frequency VCO




$$V^* = +30 \text{ V}_{\text{DC}}$$

$$+250 \text{ mV}_{\text{DC}} \leq V_C \leq +50 \text{ V}_{\text{DC}}$$

$$700 \text{ Hz} \leq f_L \leq 100 \text{ kHz}$$


TI /H/5708-5

Basic Comparator




T1/H/5709-6

Non-Inverting Comparator with Hysteresis










TI/H/5709-8

Inverting Comparator with Hysteresis




TLV/H/5708-10


Typical Applications (Continued)**Output Strobing****Large Fan-in AND Gate****AND Gate****Limit Comparator****OR Gate****Comparing Input Voltages
of Opposite Polarity**

Typical Applications (Continued)**NATL SEMICOND (LINEAR)****ORing the Outputs**


TL/H/5709-17

Zero Crossing Detector (Single Power Supply)


TL/H/5709-21

One-Shot Multivibrator




TL/H/5709-22

Bi-Stable Multivibrator

TL/H/5709-24

One-Shot Multivibrator with Input Lock Out

TL/H/5709-23

Typical Applications (Continued) ($V^+ = V_{DC}$)**NATL SEMICOND (LINEAR)****Split-Supply Applications** ($V^+ = +15 \text{ V}_{DC}$ and $V^- = -15 \text{ V}_{DC}$)**Zero Crossing Detector****Comparator With a Negative Reference**