


PIN CONFIGURATION
1. EMITTER
2. BASE
3. COLLECTOR



DIM	MIN	MAX
A	8,50	9,39
B	7,74	8,50
C	6,09	6,60
D	0,40	0,53
E	—	0,88
F	2,41	2,66
G	4,82	5,33
H	0,71	0,86
J	0,73	1,02
K	12,7	—
L	42 DEG	48 DEG

ALL DIMENSIONS ARE IN M.M.

TO-39 Metal-Can Package Transistors (NPN)

Maximum Ratings							Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)																
Type No.	V _{CB0} (V) Min	V _{CEO} (V) Min	V _{EB0} (V) Min	P _D (W) @Tc=25°C	I _C (A)	I _{CM} (A)	I _{CB0} (μA) Max	V _{CB} (V) @ I _C	I _{CES} (μA) Max	V _{CE} (V) @ I _{CES}	h _{FE}	β	I _C & V _{CE} (mA) @ I _C	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) Min	I _C (mA) Max	C _{ob} (pF) Min Max Typ	f _T (MHz) Min Typ Max	t _{off} (ns) Max	NF (dB) Max	β Freq (MHz) Max		
2N656	60	60	8				10	30			30	90	200	10	4		200						
2N657	100	100	8	1	0.5		10	30			30	90	200	10	4		200						
2N696	60	40	5	0.8	0.5		1	30			20	60	150	10	1.5	1.3	150	35					
2N697	60	40	5	0.6	0.5		1	30			40	120	150	10	1.5	1.3	150	35					
2N699	120	80	5	0.8	0.5		2	60			40	120	150	10	5	1.3	150	20	50		50		
2N1507	60	30	5	0.6	1		1	30			100	300	150	10	1.5		150	35		50			
2N1613	75	50	7	0.8	0.5		0.01	60			20		500	10	1.5	1.3	150	25	60		50	12 0.001	
											40	120	150	10									
											35		10	10									
											20		0.1	10									
2N1644	60		5	2			1	30			40		150	10	1.5	1.3	150						
2N1711	75	50	7	0.8	1		0.01	60			40		500	10	1.5	1.3	150	25	70		50	8	
											100	300	150	10									
											75		10	10									
											35		0.1	10									
											20		0.01	10									
2N1837	80	30	8	0.6	1	1	0.5	30			40	120	150	10	0.8	1.3	150	18					
2N1838	45	20	5	0.6	0.5		1.5	30			40	150	100	10	1.4	1.5	100	27					
2N1840	25	15	5	0.6		0.5	0.3	10			10		150	1.4	1.4	1.75	150	27					
											10	100	150	10									
2N1889	100	80	7	0.8			0.01	75			20		0.1	10	1.2	0.9	50	15	50		50		
											35		10	10	5	1.3	150						
											40	120	150	10									
2N1890	100	80	7	0.8			0.01	75			100	300	150	10	1.2	0.9	50	15	60		50		
															5	1.3	150						
2N1893	120	80	7	0.8	0.5	1	0.01	90			20		0.1	10	1.2	0.9	50	15	50		50		
											35		10	10	5	1.3	150						
											40	120	150	10									

TO-39 Metal-Can Package Transistors (NPN)

CDIL

Maximum Ratings							Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)																			
Type No.	V _{CBO} (V) Min	V _{CEO} (V) Min	V _{EBO} (V) Min	P _D (W) @ Tc=25°C	I _C (A)	I _{CM} (A)	I _{CBO} (μA) Max	V _{CB} (V) @ I _C	I _{CES} (μA) Max	V _{CE} (V) @ I _C	h _{FE} Min	β Max	I _C & (mA)	V _{CE} (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) & Min	I _C (mA) @	C _{ob} (pF) Min Max Typ	f _i (MHz) Min Typ	β Max	I _C (mA)	t(off) (ns) Max	NF (dB) Max	β Max	Freq (MHz) Max	
2N1972	60	30	5	0.6			1	30			110	350	50	10	2		50	25		50						
2N1973	100	80	7	0.8			0.025	75			75		10	10	1.2		50	15		60						
2N1974	100	80	7	0.8			0.025	75			35		10	10	1.2		50	15		50						
2N1975	100	80	7	0.8			0.025	75			15		10	10	1.2		50	15		40						
2N1986	50	25	5	0.6	1		5	30			60		30	10	0.6	0.9	30	20 35								
											60	240	150	10	1.5	1.3	150									
2N1987	50	25	5	0.6	1		5	30			20		30	10	0.6	0.9	30	20 35								
											20	80	150	10	1.5	1.3	150									
2N1988	100	45	5	0.6		1	5	50			35	120	30	10	2	1	30	20								
2N1989	100	45	5	0.6		1	5	50			20	60	30	10	2	1	30	20								
2N1990	100		3	0.6							20		30	10	0.5	1	2									
2N2049	75	50	7	0.8	0.5		0.01	60			100	300	150	10	0.4		10	25		50						
2N2102	120	65	7	1	1		0.002	60			10		1000	10	0.5	1.1	150	15	60		50			6	0.001	
											25		500	10												
											40	120	150	10												
											35		10	10												
											20		0.1	10												
2N2192	60	40	5	0.8	1		0.01	30			15		0.1	10	0.35	1.3	150	20	50		50					
											75		10	10												
											100	300	150	10												
											35		500	10												
											15		1000	10												
											70		150	1												
2N2193	80	50	8	0.8	1		0.01	60			15		0.1	10	0.35	1.3	150	20	50		50					
											30		10	10												
											40	120	150	10												
											20		500	10												
											15		1000	10												
											30		150	1												
2N2194	60	40	5	0.8	1		0.01	30			15		10	10	0.35	1.3	150	20	50		50					
											20	60	150	10												
											12		500	10												
											15		150	1												
2N2195	45	25	5	0.6		1	0.1	30			20		150	10	0.35	1.3	150	20	50		50					
											10		150	1												
2N2218	60	30	5	0.8	0.8		0.01	50			20		500	10	0.4	0.6	1.3	8	250		20					
											20		150	1	1.6	2.6	500									
											40	120	150	10												
											35		10	10												
											25		1	10												
											20		0.1	10												
2N2218A	75	40	6	0.8	0.8		0.01	60	* 0.01	60	20		0.1	10	0.3	0.6	1.2	8	300		20					
											25		1	10	1		2	500								
											35		10	10												
											40	120	150	10												
											20		150	1												
											25		500	1												
2N2219	60	30	5	0.8	0.8		0.01	50			35		0.1	10	0.4	0.6	1.3	8	250		20					
											50		1	10	1.6	2.6	500									
											75		10	10												
											100	300	150	10												
											50		150	1												
											30		500	1												

* NOTE: I_{CEX}

Maximum Ratings							Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)																			
Type No.	V _{CB0} (V) Min	V _{CEO} (V) Min	V _{EB0} (V) Min	P _D (W) @Tc=25°C	I _C (A)	I _{CM} (A)	I _{CB0} (μA) Max	V _{CB} @ (V)	I _{CES} (μA) Max	V _{CE} @ (V)	h _{FE} @ Min Max	I _C & (mA)	V _{CE} (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) & Min Max	I _C @ (mA)	C _{ob} (pF) Min Max Typ	f _T (MHz) Min Typ Max	I _C (mA)	t(off) (ns) Max	NF (dB) Max	@ Freq (MHz)				
2N2219A	75	40	6	0.8	0.8		0.01	60	* 0.01	60	35 50 75 100 50 40	 300 150 500	0.1 1 10 10 1 1	10 10 10 10 1 1	0.3 1	0.6 2	1.2 500	8	300		20					
2N2243	120	80	7	0.8	1		0.01	60			15 40 30 30 15	 120 150 0.1	500 150 10 150 10	10 10 10 1 10	0.35		1.3 150	15	50		50					
2N2270	60	45	7	1	1		0.05	60			50 30	200 1	150 10	10 10	0.9		1.2 150	15	100		50	10	0.001			
2N2440	120	80	7	0.8	0.5		0.001	90			35 100	 300	0.1 150	10 10	0.4 3		0.9 1.3	50 150	15							
2N3019	140	80	7	0.8		1	0.01	90			50 90 100 50 15	 300 1	0.1 10 150 500 1	10 10 10 10 10	0.2 0.5		1.1 500	12	100	400	50	4	0.001			
2N3020	140	80	7	0.8		1	0.01	90			30 40 40 30 15	100 120 120 100 1000	0.1 10 150 500 10	10 10 10 10 10	0.2 0.5		1.1 500	12	80		50					
2N3053	60	40	5	5	0.7				* 0.25	30	50 25	250 150	150 150	10 2.5	1.4		1.7 150	15		100	50					
2N3300	60	30	5	0.8	0.5				0.01	50	50 50 100 75 50 35	 300 1 10 0.1	500 150 150 10 1 10	10 1 10 10 10 10	0.22 0.6		1.1 1.5	150 500	8	250		50	150			
2N3440	300	250	7	1	1		20	360			40	160	20	10	0.5		1.3 50	10		15	10					
2N3498	100	100	6	1.0	0.5		0.05	50			20 25 35 40 15 95	 120 500 300	0.1 1 10 150 10 10	10 10 10 10 10 10	0.6 0.2 0.25		1.4 0.8 0.9	300 10 50	10	150		20				
2N3499	100	100	6	1	0.5		0.05	50			35 50 75 100 20 20	 300 150 500 300	0.1 1 10 10 10 10	10 10 10 10 10 10	0.2 0.25 0.6		0.8 0.9 1.4	10 50 300	10	150		20				
2N3500	150	150	6	1	0.3		0.05	75			20 25 35 40 15 15	 120 150 300 500	0.1 1 10 10 10 10	10 10 10 10 10 10	0.2 0.25 0.4		0.8 0.9 1.2	10 50 150	8	150		20				

* NOTE: I_{CEX}

TO-39 Metal-Can Package Transistors (NPN)

CDIL

Maximum Ratings							Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)																
Type No.	V _{CBO} (V) Min	V _{CEO} (V) Min	V _{EBO} (V) Min	P _D (W) @ Tc=25°C	I _C (A)	I _{CM} (A)	I _{CBO} (μA) Max	V _{CB} (V) @ (V)	I _{CES} (μA) Max	V _{CE} (V) @ (V)	h _{FE} Min	β Max	I _C & (mA)	V _{CE} (V) (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) & Min	I _C (mA) @ (mA)	C _{ob} (pF) Min Max Typ	f _T (MHz) Min Typ Max	I _C (mA) (mA)	t(off) (ns) Max	NF (dB) Max	β Freq (MHz) Max
2N3501	150	150	6	1	0.3		0.05	75			35		0.1	10	0.4	1.2	150	8	150	20			
											50		1	10	0.2	0.8	10						
											100	300	150	10	0.25	0.9	50						
											20		300	10									
											75		10	10									
											20		500	10									
2N3678	75	55	6	0.8	0.8		0.01	60			25		500	10	0.4	.6	1.2	150			250		
											20		150	1	1	2	500						
											40	120	150	10									
											35		10	10									
											25		1	10									
											20		0.1	10									
2N3742	300	300	7	1	0.05		0.2	200			10		3	10	0.75	1	10	6	30	10			
											15		10	10	1	1.2	30						
											20	200	30	10									
											20		50	20									
2N4237	50	40	6	1	1		0.01	50			15		1000	1	0.6	1.5	1000	100					
											30		500	1	0.3		500						
											30	150	250	1									
											30		50	1									
2N4926	200	200	7	1	0.05		0.1	100			10		3	10	1	1.2	10		30	300	10		
											15		10	10	2		30						
											20	200	30	10		1.5	50						
											20		50	20									
2N5320	100	75	7	10	2				*100	100	30	130	500	4	0.5	1.1	500				800		
											10		1000	2									
2N5321	75	50	5	10	2				*100	75	40	250	500	4	0.8	1.4	500				800		
2N5681	100	100	4	1	1		1	100	* 1	100	5		1000	2	0.6		250	50	30	100			
											40	150	250	2	1		500						
															2		1						
2N5682	120	120	4	1	1		1	120	* 1	120	5		1000	2	0.6		250	50	30	100			
											40	150	250	2	1		500						
BC140	80	40	7	0.8	1				0.1	60	40	400	100	1	1		1000	25	50	50	850		
BC140-6	80	40	7	0.8	1				0.1	60	40	100	100	1	1		1000	25	50	50	850		
BC140-10	80	40	7	0.8	1				0.1	60	63	160	100	1	1		1000	25	50	50	850		
BC140-16	80	40	7	0.8	1				0.1	60	100	250	100	1	1		1000	25	50	50	850		
BC141	100	60	7	0.8	1				0.1	60	40	400	100	1	1		1000	25	50	50	850		
BC141-6	100	60	7	0.8	1				0.1	60	40	100	100	1	1		1000	25	50	50	850		
BC141-10	100	60	7	0.8	1				0.1	60	63	160	100	1	1		1000	25	50	50	850		
BC141-16	100	60	7	0.8	1				0.1	60	100	250	100	1	1		1000	25	50	50	850		
BC300	120	80	7	0.85	0.5		0.02	120			40	240	150	10	0.5		150		100	400	50		
BC300-4	120	80	7	0.85	0.5		0.02	120			40	80	150	10	0.5		150		100	400	50		
BC300-5	120	80	7	0.85	0.5		0.02	120			70	140	150	10	0.5		150		100	400	50		

* NOTE : ICES

Maximum Ratings							Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)																
Type No.	V _{CEO} (V) Min	V _{CE0} (V) Min	V _{EB0} (V) Min	P _D (W) @ Tc=25°C	I _C (A)	I _{CM} (A)	I _{CBO} (μA) Max	V _{CB} (V) @ I _C	I _{CES} (μA) Max	V _{CE} (V) @ I _C	h _{FE} Min	β Max	I _C & (mA)	V _{CE} (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) Min	I _C (mA) @	C _{ob} (pF) Min Max Typ	f _t (MHz) Min Typ Max	I _C (mA) @	t(off) (ns) Max	NF (dB) Max	Q Freq (MHz) Max
BC300-6	120	80	7	0.85	0.5		0.02	120			120	240	150	10	0.5		150		100	400			
BC301	90	60	7	0.85	0.5		0.02	90			40	240	150	10	0.5		150		100	400	50		
BC301-4	90	60	7	0.85	0.5		0.02	90			40	80	150	10	0.5		150		100	400	50		
BC301-5	90	60	7	0.85	0.5		0.02	90			70	140	150	10	0.5		150		100	400	50		
BC301-6	90	60	7	0.85	0.5		0.02	90			120	240	150	10	0.5		150		100	400	50		
BC302	60	45	7	0.85	0.5		0.02	60			40	240	150	10	0.5		150		100	400	50		
BC302-4	60	45	7	0.85	0.5		0.02	60			40	80	150	10	0.5		150		100	400	50		
BC302-5	60	45	7	0.85	0.5		0.02	60			70	140	150	10	0.5		150		100	400	50		
BC302-6	60	45	7	0.85	0.5		0.02	60			120	240	150	10	0.5		150		100	400	50		
BD115	245	180	5	0.875	0.2						22		50	10	9		100						
BF257	160	160	5	1	0.1		0.05	100			25		30	10	1		30	3.5	110	30			3.5
BF258	250	250	5	1	0.1		0.05	200			25		30	10	1		30		110	30			
BF259	300	300	5	1	0.1		0.05	250			25		30	10	1		30		110	30			
BF336	185	180	5	0.8		0.2					20		30	10					80	130	30		
BF337	250	200	5	0.8		0.2					20		30	10					80		30		
BF338	300	225	5	0.8	0.2						20		30	10					80	130	30		
BFX84	45	45	6	0.8	1		0.5	100			15		1000	10	0.15	1.2	10	12	50		50	360	
											20		500	10	0.35	1.3	150						
											30		150	10	1	1.5	500						
											20		10	10	1.6	2	1000						
BFX85	100	60	6	0.8	1		0.5	100			15		1000	10	0.15	1.2	10	12	50		50		
							0.05	80			30		500	10	0.35	1.3	150						
											70		150	10	1	1.5	500						
											50		10	10	1.6	2	1000						
BFX86	45	45	6	0.8	1		0.05	30			15		1000	10	0.15	1.2	10	12	50		50	360	
											30		500	10	0.35	1.3	150						
											70		150	10	1	1.5	500						
											50		10	10	1.6	2	1000						
BFY50	80	35	6	0.8	1		0.05	60			20		10	6	0.2		150	12	60		50		
											30		150	6	1	2	1000						
											15		1000	6									
BFY51	60	30	6	0.8	1		0.05	40			30		10	6	0.35		150	12	50		50		
											40		150	6	1.6	2	1000						
											15		1000	6									
BFY52	40	20	6	0.8	1		0.05	30			30		10	6	0.35		150	12	50		50		
											60		150	6	1.6	2	1000						
											15		1000	6									
BFY56	85	45	7	0.8	1				0.02	50	15		0.1	10	0.3	1.5	150	25	40		50		
											20		500	10	1.2	2.3	1000						
											30	150	150	1									

TO-39 Metal-Can Package Transistors (NPN)

CDIL

Maximum Ratings							Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)																						
Type No.	V _{CBO} (V) Min	V _{CEO} (V) Min	V _{EBO} (V) Min	P _D (W) @ Tc=25°C	I _C (A)	I _{CM} (A)	I _{CBO} (μA) Max	V _{CB} @ (V)	I _{CES} (μA) Max	V _{CE} @ (V)	h _{FE} Min	@ Max	I _C & (mA)	V _{CE} (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & (V) Min	V _{BE(SAT)} (V) Max	I _C @ (mA)	C _{ob} (pF) Min	Max	Typ	f _T (MHz) Min	@ Typ	Max	I _C (mA) Max	t(off) (ns) Max	NF (dB) Max	@ Freq (MHz) Max	
BFY72	50	28	5	0.8	0.7		0.04	20			15		0.1	10	0.25		1.2	150		8			50			50			
											20		1	10	0.7		1.6	500											
											30		10	10															
											40	150	150	10															
											15		500	10															
BSX45	# 80	40	7	1	1				0.01	60	40	250	100	1	1			1000		25			50			50	850		
BSX45-6	# 80	40	7	1	1				0.01	60	10		0.1	1	1			1000		25			50			50	850		
											40	100	100	1															
											15		500	1															
BSX45-10	# 80	40	7	1	1				0.01	60	15		0.1	1	1			1000		25			50			50	850		
											63	160	100	1															
											25		500	1															
BSX45-16	# 80	40	7	1	1				0.01	60	25		0.1	1	1			1000		25			50			50	850		
											100	250	100	1															
											35		500	1															
BSX46	# 100	60	7	1	1				0.01	60	40	250	100	1	1			1000		20			50			50	850		
BSX46-6	# 100	60	7	1	1				0.01	60	10		0.1	1	1			1000		20			50			50	850		
											40	100	100	1															
											15		500	1															
BSX46-10	# 100	60	7	1	1				0.01	60	15		0.1	1	1			1000		20			50			50	850		
											63	160	100	1															
											25		500	1															
BSX46-16	# 100	60	7	1	1				0.01	60	25		0.1	1	1			1000		20			50			50	850		
											100	250	100	1															
											35		500	1															
BSX47	# 120	80	7	1	1				0.01	80	40	250	100	1	1			1000		15			50			50	850		
BSX47-6	# 120	80	7	1	1				0.01	80	1		0.1	1	1			1000		15			50			50	850		
											40	100	100	1															
											15		500	1															
BSX47-10	# 120	80	7	1	1				0.01	80	15		0.1	1	1			1000		15			50			50	850		
											63	160	100	1															
											25		500	1															
BSX47-16	# 120	80	7	1	1				0.01	80	25		0.1	1	1			1000		1	5		50			50	850		
											100	250	100	1															
											35		500	1															
BSX62	# 60	40	5	5	3				0.1	40	40	250	1000	1	0.8		1.3	2000		70			30			300			
															0.7		1.2	1000											
BSX62-6	# 60	40	5	5	3				0.1	40	30		100	1	0.8		1.3	2000		70			30			200			
											40	100	1000	1	0.7		1.2	1000											
											25		2000	5															
BSX62-10	# 60	40	5	5	3				0.1	40	30		100	1	0.8		1.3	2000		70			30			200			
											63	160	1000	1	0.7		1.2	1000											
											25		2000	5															
BSX62-16	# 60	40	5	5	3				0.1	40	30		100	1	0.8		1.3	2000		70			30			200			
											100	250	1000	1	0.7		1.2	1000											
											25		2000	5															
BSX63	# 80	60	5	5	3				0.1	60	4	250	1000	1	0.8		1.3	2000		70			30			200			
															0.7		1.2	1000											

NOTE: V_{CES}

Maximum Ratings							Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)																						
Type No.	V _{CBO} (V) Min	V _{CEO} (V) Min	V _{EBO} (V) Min	P _D (W) @Tc=25°C	I _C (A)	I _{CM} (A)	I _{CBO} (μA) Max	V _{CB} @ (V)	I _{CES} (μA) Max	V _{CE} @ (V)	h _{FE} Min	β Max	I _C & (mA)	V _{CE} (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & (V) Min	V _{BE(SAT)} (V) Max	I _C @ (mA)	C _{ob} (pF) Min	Max	Typ	f _t (MHz) Min	β Typ	I _C (mA) Max	t(off) (ns) Max	NF (dB) Max	β Max	Freq (MHz) Max	
BSX63-6	# 80	60	5	5	3				0.1	60	30		100	1	0.8		1.3	2000	70			30		200					
											40	100	1000	1	0.7		1.2	1000											
											25		2000	5															
BSX63-10	# 80	60	5	5	3				0.1	60	30		100	1	0.8		1.3	2000	70			30		200					
											63	160	1000	1	0.7		1.2	1000											
											25		2000	5															
BSX63-16	# 80	60	5	5	3				0.1	60	30		100	1	0.8		1.3	2000	70			30		200					
											100	250	1000	1	0.7		1.2	1000											
											25		2000	5															
BSY51	60	35	5	0.8	0.5				0.1	30	40	120	150	10	1		1.3	150	9			130		50					
BSY52	60	25	5	0.8	0.5				0.1	30	100	300	150	10	1		1.3	150	9			130		50					
BSY53	75	30	7	0.8	0.75				0.01	60	20		0.1	10	0.6		1.2	150				150		50					
											35		10	10	1.2		500												
											40	120	150	10															
											20		500	10															
BSY54	75	30	7	0.8	0.75				0.01	60	35		0.1	10	0.6		1.3	150				150		50					
											75		10	10															
											100	300	150	10															
											40		500	10															
CL21	20	20	5	0.75			0.5	15			150	350	100	3	0.6		150						80						
CL100	60	50	5	0.8		1	0.05	40			50	280	150	10	0.6		150												
CL150	35	30	5	0.8			0.05	25			50	280	150	1	0.6		150												

NOTE: V_{CES}

TO-39 Metal-Can Package Transistors (PNP)

CDIL

Maximum Ratings							Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)																						
Type No.	V _{CBO} (V) Min	V _{CEO} (V) Min	V _{EB0} (V) Min	P _D (W) @ Tc=25°C	I _C (A)	I _{CM} (A)	I _{CBO} (μA) Max	V _{CB} @ (V)	I _{CES} (μA) Max	V _{CE} @ (V)	h _{FE} Min	@ Max	I _C & (mA)	V _{CE} (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & Min	V _{BE(SAT)} (V) Max	I _C @ (mA)	C _{ob} (pF) Min	Max	Typ	f _T (MHz) Min	@ Typ	I _C (mA) Max	t(off) (ns) Max	NF (dB) Max	@ Max	Freq (MHz)	
2N2904	60	40	5	0.6	0.6		0.02	50			20		500	10	0.4		1.3	150		8			200		50	100			
											40	120	150	10	1.6		2.6	500											
											35		10	10															
											25		1	10															
											20		0.1	10															
2N2904A	60	60	5	0.6	0.6		0.01	50			40		500	10	0.4		1.3	150		8			200		50	100			
											40	120	150	10	1.6		2.6	500											
											40		10	10															
											40		1	10															
											40		0.1	10															
2N2905	60	40	5	0.6	0.6		0.02	50			30		500	10	0.4		1.3	150		8			200		50	100			
											100	300	150	10	1.6		2.6	500											
											75		10	10															
											50		1	10															
											35		0.1	10															
2N2905A	60	60	5	0.6	0.6		0.01	50			50		500	10	0.4		1.3	150		8			200		50	100			
											100	300	150	10	1.6		2.6	500											
											100		10	10															
											100		1	10															
											75		0.1	10															
2N3072	60	60	4	0.8	0.5				0.01	30	15		300	2	0.25		1.2	50		10			130		50	100			
											30	130	50	1	1		2	300											
2N3073	60	60	4						0.01	30	15		300	2	0.25		1.2	50		10			130		50	100			
											30	130	50	1	1		2	300											
2N3502	45	45	5	0.6	0.6		0.01	30			50		500	10	0.25		1	50		8			200		50	100	4		
											100	300	150	10	0.4		1.3	150											
											140		10	10	1.6		2	500											
											135		1	10															
											120		0.1	10															
											80		0.01	10															
2N3503	60	60	5	0.6	0.6		0.01	50			50		500	10	0.25		1	50		8			200		50	100	4		
											100	300	150	10	0.4		1.3	150											
											140		10	10	1.6		2	500											
											135		1	10															
											120		0.1	10															
											80		0.01	10															
2N3635	140	140	5	1	1		0.1	100			80		0.1	10	0.3		0.8	10		10			200		30	600	3	0.001	
											90		1	10	0.5	0.65	0.9	50											
											100		10	10															
											100	300	50	10															
											50		150	10															
2N3636	175	175	5	1	1		0.1	100			40		0.1	10	0.3		0.8	10		10			150		30	600	3	0.001	
											45		1	10	0.5	0.65	0.9	50											
											50		10	10															
											50	150	50	10															
											25		150	10															
2N3637	175	175	5	1	1		0.1	100			80		0.1	10	0.3		0.8	10		10			200		30	600	3	0.001	
											90		1	10	0.5	0.65	0.9	50											
											100		10	10															
											100	300	50	10															
											50		150	10															
2N4030	60	60	5	0.8		1	0.05	50			15		1000	5	1			1000		20									
											25		500	5	0.5			500											
											40	120	100	5	0.15		0.9	150											
											30		0.1	5															

Maximum Ratings							Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)																	
Type No.	V _{CBO} (V) Min	V _{CEO} (V) Min	V _{EB0} (V) Min	P _D (W) @Tc=25°C	I _C (A)	I _{CM} (A)	I _{CBO} (μA) Max	V _{CB} @ (V)	I _{CES} (μA) Max	V _{CE} @ (V)	h _{FE} @ Min Max	I _C & (mA)	V _{CE} (V)	V _{CE(SAT)} (V) Max Min	V _{BE(SAT)} (V) Max Min	I _C @ (mA)	C _{ob} (pF) Min Max Typ	f _i (MHz) Min Typ Max	t _{off} (ns) Max	NF (dB) Max	@ Freq. (MHz)			
2N4031	80	80	5	0.8		1	0.05	60			10 1000 25 500 40 120 100 30 0.1 5	5	5	5	0.5 0.9	500 150	20							
2N4032	60	60	5	0.8		1	0.05	50			40 1000 70 500 100 300 100 75 0.1 5	5	5	5	1 0.5 0.15	1000 500 150	20							
2N4033	80	80	5	0.8		1	0.05	60			25 1000 70 500 100 300 100 75 0.1 5	5	5	5	0.5 0.9	500 150	20							
2N4036	90	65	7	1	1		0.02	90			20 500 40 140 150 20 0.1 10	10	10	10	0.65 1.4	150	700							
2N4037	60	40	7	1	1		0.25	60			50 250 15 1 10	10	10	1.4		150								
2N4314	90	65		1	1		0.25	60			50 250 15 1 10	10	10	1.4		150	30	60		50				
2N5322	100	75	7	1					*100	100	30 130 10 1000	500	4	0.7	1.1	500				1000				
2N5323	75	50	5	10	2				*100	75	40 250 500	4	4	1.2	1.4	500				1000				
2N5415	200	200	4	1	1		50	175			30 150 50	10	10				15							
2N5416	350	300	6	1	1		50	280			30 120 50	10	10				15							
2N5679	100	100	4	1	1		1	100	* 1	100	5 1 40 150 250	2	2	0.6 1 2		250 500 1000	50	30		100				
2N5680	120	120	4	1	1		1	120	* 1	120	5 1000 40 150 250	2	2	0.6 1 2		250 500 1000	50	30		100	10			
BC160	40	40	5	0.8	1				0.1	40	40 400 100	1	1	1		1000	30	50		50	650			
BC160-6	40	40	5	0.8	1				0.1	40	40 100 100	1	1	1		1000	25	50		50	850			
BC160-10	40	40	5	0.8	1				0.1	40	63 160 100	1	1	1		1000	25	50		50	850			
BC160-16	40	40	5	0.8	1				0.1	40	100 250 100	1	1	1		1000	25	50		50	850			
BC161	60	60	5	0.8	1				0.1	60	40 400 100	1	1	1		1000	30	50		1	650			
BC161-6	60	60	5	0.8	1				0.1	60	40 100 100	1	1	1		1000	25	50		50	850			
BC161-10	60	60	5	0.8	1				0.1	60	63 160 100	1	1	1		1000	25	50		50	850			
BC161-16	60	60	5	0.8	1				0.1	60	100 250 100	1	1	1		1000	30	50		50	650			
BC303	85	60	7	0.85	0.5		0.02	85			40 240 150	10	10	0.65		150		75		400	50			
BC303-4	85	60	7	0.85	0.5		0.02	85			40 80 150	10	10	0.65		150		75		400	50			
BC303-5	85	60	7	0.85	0.5		0.02	85			70 140 150	10	10	0.65		150		75		400	50			

* NOTE: I_{CES}

TO-39 Metal-Can Package Transistors (PNP)

CDIL

Maximum Ratings							Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)																					
Type No.	V _{CBO} (V) Min	V _{CEO} (V) Min	V _{EBO} (V) Min	P _D (W) @Tc=25°C	I _C (A)	I _{CM} (A)	I _{CBO} (μA) Max	V _{CB} (V) @	I _{CES} (μA) Max	V _{CE} (V) @	h _{FE} Min	β Max	I _C & (mA)	V _{CE} (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) & Min	I _C (mA) Max	C _{ob} (pF) Min	Max	Typ	f _i (MHz) Min	Typ	Max	t(off) (ns) Max	NF (dB) Max	β Max	Freq (MHz) Max	
BC303-6	85	60	7	0.85	0.5		0.02	85			120	240	150	10	0.65		150					75	400	50				
BC304	60	45	7	0.85	0.5		0.02	60			40	240	150	10	0.65		150					75	400	50				
BC304-4	60	45	7	0.85	0.5		0.02	60			40	80	150	10	0.65		150					75	400	50				
BC304-5	60	45	7	0.85	0.5		0.02	60			70	140	150	10	0.85		150					75	400	50				
BC304-6	60	45	7	0.85	0.5		0.02	60			120	240	150	10	0.65		150					75	400	50				
BFX29	20	15	5	0.5	0.6		0.05	50			40		150	10	0.4		1.3	150	12		100		50	150				
											50		50	10			0.9	30										
											50		10	10														
											40		1	10														
											20		0.1	10														
BFX30	65	65	5	0.5	0.6		0.05	50			10		150	0.4			0.9	30	12					290				
											20		50	0.4			1.3	150										
											50	200	10	0.4														
											40		1	0.4														
BFX38	55	55	5	0.8	1		0.05	40			60		0.1	5	0.15		0.9	150	20		100		50	350				
											85		100	5	0.5		1.1	500										
											60		500	5														
											30		1000	5														
BFX40	75	75	5	0.8	1		0.05	50			60		0.1	5	0.15		0.9	150	20		100		50	350				
											85		100	5	0.5		1.1	500										
											60		500	5														
											25		1000	5														
BFX41	75	75	5	0.8	1		0.05	50			35		0.1	5	0.15		0.9	150	20		100		50					
											40		100	5	0.5		1.1	500										
											25		500	5														
											10		1000	5														
BFX87	45	50	6	0.6	0.6		0.05	40			25		500	10	0.4		1.3	150	12		100		50	150				
											40		150	10	0.9			30										
											40		10	10														
											40		1	10														
BFX88	45	40	6	0.8	0.8		0.05	30			25		500	10	0.4		1.3	150	12		100		50	150				
											40		150	10			0.9	30										
											40		10	10														
											40		1	10														
CK100	60	50	5	0.8	1		0.05	40			50	280	150	10	0.6			150										
CK150	35	30	5	0.8			0.05	25			50	280	150	1	0.6			150										