



Description

PT 2272 is a remote control decoder paired with PT 2262 utilizing CMOS Technology. It has 12 bits of tri-state address pins providing a maximum of 531,441 (or 3^{12}) address codes; thereby, drastically reducing any code collision and unauthorized code scanning possibilities. PT 2272 is available in several options to suit every application need : variable number of data output pins, latch or momentary output type.

Features


- ☐ CMOS Technology
- ☐ Low Power Consumption
- ☐ Very High Noise Immunity
- ☐ Up to 12 Tri-State Code Address Pins
- ☐ Up to 6 Data Pins
- ☐ Wide Range of Operating Voltage: $V_{cc} = 4 \sim 15$ Volts
- ☐ Single Resistor Oscillator
- ☐ Latch or Momentary Output Type
- ☐ Available in DIP and SO Package

Applications


- ☐ Car Security System
- ☐ Garage Door Controller
- ☐ Remote Control Fan
- ☐ Home Security/Automation System
- ☐ Remote Control Toys
- ☐ Remote Control for Industrial Use




Pin Configuration




PT 2272




PT 2272A - M2/L2




PT 2272 - M3/L3



PT 2272 - M4/L4



PT 2272 - M5/L5




PT 2272 - M6/L6




Remote Control Decoder


PT 2272




PT 2272 (20 Pins)




PT 2272A - M2/L2 (20 Pins)




PT 2272 - M3/L3 (20 Pins)



PT 2272 - M4/L4 (20 Pins)



PT 2272 - M5/L5 (20 Pins)




PT 2272 - M6/L6 (20 Pins)



URL: <http://www.princeton.com.tw>

PT 2272

PT2272 (No Data)RF Application






URL: <http://www.princeton.com.tw>

PT 2272

[illegible]



PT2272 (4 Data) IR Application Circuit





Ordering Information

A. 18-Pin Package:

Part No.	Data Bit(s)	Output Type	Package
PT2272 (-S18)	None	*	DIP (SO)
PT2272A-L2 (-S18)	2	Latch	DIP (SO)
PT2272A-M2 (-S18)	2	Momentary	DIP (SO)
PT2272-L3 (-S18)	3	Latch	DIP (SO)
PT2272-M3 (-S18)	3	Momentary	DIP (SO)
PT2272-L4 (-S18)	4	Latch	DIP (SO)
PT2272-M4 (-S18)	4	Momentary	DIP (SO)
PT2272-L5 (-S18)	5	Latch	DIP (SO)
PT2272-M5 (-S18)	5	Momentary	DIP (SO)
PT2272-L6 (-S18)	6	Latch	DIP (SO)
PT2272-M6 (-S18)	6	Momentary	DIP (SO)

B. 20-Pin Package

Part No.	Data Bit(s)	Output Type	Package
PT2272-S	None	*	SO
PT2272A-L2S	2	Latch	SO
PT2272A-M2S	2	Momentary	SO
PT2272-L3S	3	Latch	SO
PT2272-M3S	3	Momentary	SO
PT2272-L4S	4	Latch	SO
PT2272-M4S	4	Momentary	SO
PT2272-L5S	5	Latch	SO
PT2272-M5S	5	Momentary	SO
PT2272-L6S	6	Latch	SO
PT2272-M6S	6	Momentary	SO

Note: * = use VT (Valid Transmission)



PT 2272 X - X X X

